



**HAL**  
open science

## Gaussian Beams

Nicolas Fressengeas

► **To cite this version:**

Nicolas Fressengeas. Gaussian Beams. DEA. Gaussian Beams, Université de Lorraine, 2012. cel-00670322v1

**HAL Id: cel-00670322**

**<https://cel.hal.science/cel-00670322v1>**

Submitted on 15 Feb 2012 (v1), last revised 10 Dec 2012 (v3)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# UE SPM-PHY-S07-101

## Gaussian Beams

N. Fressengeas

Laboratoire Matériaux Optiques, Photonique et Systèmes  
Unité de Recherche commune à l'Université Paul Verlaine Metz et à Supélec

Download this document from  
<http://moodle.univ-metz.fr/>

## Further reading

[KL66, GB94]



A. Gerrard and J.M. Burch.

*Introduction to matrix methods in optics.*  
Dover, 1994.



H. KOGELNIK and T. LI.

Laser beams and resonators.

*Appl. Opt.*, 5(10):1550–1567, Oct 1966.

# Course Outline

- 1 Fundamentals of Gaussian beam propagation
  - Gaussian beams vs. plane waves
  - The fundamental mode
  - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
  - Linear algebra for geometrical optics
  - A few simple matrices
  - Matrix method for Gaussian beams

- 1 Fundamentals of Gaussian beam propagation
  - Gaussian beams vs. plane waves
  - The fundamental mode
  - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
  - Linear algebra for geometrical optics
  - A few simple matrices
  - Matrix method for Gaussian beams

# Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

## Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves

# Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

## Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and **power density**, are also homogeneous
- Total carried power is infinite

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves

# Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

## Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- **Total carried power is infinite**

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves
- To what extent can we assume they are plane waves ?



# Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

## Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

## Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves
- To what extent can we assume they are plane waves ?

# Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

## Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

## Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves
- **To what extent can we assume they are plane waves ?**

## Plane waves, Gaussian beams. . . what else ?

Solutions of the wave equations: one finds only those he was searching for

### Solving the wave equation

$$\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$$

- Vectorial Partial Derivatives Equations
- Solutions are numerous
- An **ansatz**<sup>1</sup> is needed to seek solutions

### Gaussian beams as an *ansatz*

- We will find another family of solutions
- We never pretend to get them all

---

<sup>1</sup>An ansatz is an *a priori* hypothesis on the form of the sought solution.

## Plane waves, Gaussian beams. . . what else ?

Solutions of the wave equations: one finds only those he was searching for

### Solving the wave equation

$$\overline{\Delta} \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$$

- Vectorial Partial Derivatives Equations
- Solutions are numerous
- An **ansatz**<sup>1</sup> is needed to seek solutions

### Gaussian beams as an *ansatz*

- We will find another **family of solutions**
- We never pretend to get them all

---

<sup>1</sup>An ansatz is an *a priori* hypothesis on the form of the sought solution.

## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : complex beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our new unknown

Envelope equation

## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k}\cdot\vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : **complex** beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our new unknown

### Envelope equation

- Wave equation:  $\Delta \vec{E} = -\frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation:  $\Delta E + E = 0$
- Plane wave:  $\Delta e^{-i\vec{k}\cdot\vec{r}} = -k^2 e^{-i\vec{k}\cdot\vec{r}}$

## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k}\cdot\vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : **complex** beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our **new unknown**

### Envelope equation

- Wave equation:  $\Delta \vec{E} = -\frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation:  $\Delta E + E = 0$
- Envelope equation:  
 $\Delta u(x, y, z) e^{-ikz} + k^2 u(x, y, z) e^{-ikz} = 0$

## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k}\cdot\vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : **complex** beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our **new unknown**

### Envelope equation

- Wave equation:  $\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation:  $\Delta E + \frac{\omega^2}{c^2} E = 0$
- Envelope equation:  
 $\Delta [u(x, y, z) e^{-ikz}] + k^2 u(x, y, z) e^{-ikz} = 0$



## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k}\cdot\vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : **complex** beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our **new unknown**

### Envelope equation

- Wave equation:  $\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation:  $\Delta E + k^2 E = 0$
- Envelope equation:  
 $\Delta [u(x, y, z) e^{-ikz}] + k^2 u(x, y, z) e^{-ikz} = 0$

## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : **complex** beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our **new unknown**

### Envelope equation

- Scalar harmonic wave equation:  $\Delta E + k^2 E = 0$
- Envelope equation:  $\frac{\partial^2(u e^{-ikz})}{\partial z^2} + \Delta_{\perp} u e^{-ikz} + k^2 u e^{-ikz} = 0$

## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k}\cdot\vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : **complex** beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our **new unknown**

### Envelope equation

- Scalar harmonic wave equation:  $\Delta E + k^2 E = 0$
- Envelope equation:  $e^{-ikz} (\Delta u - 2ik \frac{\partial u}{\partial z}) = 0$

## Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

### Introducing a space dependent envelope

- Plane wave:  $\vec{E}_0 \times e^{-i\vec{k}\cdot\vec{r}}$
- Gaussian ansatz :  $u(x, y, z) \vec{e}_x \times e^{-ikz}$ 
  - $u(x, y, z)$  : **complex** beam envelope
  - $\vec{e}_x$  unit vector
- The envelope  $u(x, y, z)$  is our **new unknown**

### Envelope equation

- Scalar harmonic wave equation:  $\Delta E + k^2 E = 0$
- Envelope equation:  $\Delta u - 2ik \frac{\partial u}{\partial z} = 0$


# The paraxial approximation

Also known as Gauss conditions, Slow Varying Envelope. . .

Non Paraxial Beam



Paraxial Beam




# Paraxial approximation and partial derivatives


Assuming small angles is equivalent to neglecting  $z$  derivatives

Transversal variation vs. longitudinal variation

Non Paraxial Beam



Paraxial Beam




## Paraxial approximation and partial derivatives


Assuming small angles is equivalent to neglecting  $z$  derivatives

Transversal variation vs. longitudinal variation

Non Paraxial Beam



Paraxial Beam



Transversal Laplacian

$$\frac{\partial^2}{\partial z^2} \ll \frac{\partial^2}{\partial x^2}$$


$$\Delta \approx \Delta_{\perp}$$

## Paraxial approximation and partial derivatives


Assuming small angles is equivalent to neglecting  $z$  derivatives

Transversal variation vs. longitudinal variation

Non Paraxial Beam



Paraxial Beam



Paraxial wave equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$



- 1 Fundamentals of Gaussian beam propagation
  - Gaussian beams vs. plane waves
  - The fundamental mode
  - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
  - Linear algebra for geometrical optics
  - A few simple matrices
  - Matrix method for Gaussian beams

# A first solution to the paraxial wave equation

The simplest one, though probably the more important

## Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

### Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations

• Choosing  $q = iR_0$  at  $z = 0$

•  $q(z) = iR_0 \left( 1 + \frac{z^2}{R_0^2} \right)$

### A simple *ansatz*

$$u = e^{-i \left( P(z) + \frac{k}{2q(z)} r^2 \right)}$$

### Phase shift $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$

# A first solution to the paraxial wave equation

The simplest one, though probably the more important

## Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius  $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz:  $q' = i$

## A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

Phase shift  $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$

# A first solution to the paraxial wave equation

The simplest one, though probably the more important

## Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

## A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

## Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz:  $q' = 1$
- Integration:  $q(z) = q(0) + z$

## Phase shift

$P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$

# A first solution to the paraxial wave equation

The simplest one, though probably the more important

## Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

## A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

## Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz:  $q' = 1$
- Integration:  $q(z) = q(0) + z$

## Phase shift $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$

# A first solution to the paraxial wave equation

The simplest one, though probably the more important

## Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

## A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

## Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz:  $q' = 1$
- Integration:  $q(z) = q(0) + z$

## Phase shift $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$

# A first solution to the paraxial wave equation

The simplest one, though probably the more important

## Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

## A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

## Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz:  $q' = 1$
- Integration:  $q(z) = q(0) + z$

## Phase shift $P(z)$

- Phase shift **with respect** to the plane wave
- $qP' + i = 0$

# A first solution to the paraxial wave equation

The simplest one, though probably the more important

## Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

## A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

## Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz:  $q' = 1$
- Integration:  $q(z) = q(0) + z$

## Phase shift $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$



## The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

## The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

## The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)} - i \frac{k\lambda r^2}{2\pi W(z)^2}\right)}$$

## The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)} - i \frac{r^2}{W(z)^2}\right)}$$

# The complex beam radius

$$q(z)$$

A closer look to the signification on a complex parameter


$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$



## The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$

What is  $R$  ?

## Spherical wavefront of radius $R$ at abscissa $z$


### Phase at abscissa $z$

- Constant phase on sphere
- Phase  $\propto d$ ,  $r \ll R$

### Gaussian ansatz

- $u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$

### $R$ radius spherical wavefront



## Spherical wavefront of radius $R$ at abscissa $z$


### Phase at abscissa $z$

- Constant phase on sphere
- Phase  $\propto d$ ,  $r \ll R$

### Gaussian ansatz

$$\bullet u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$

### $R$ radius spherical wavefront





## Spherical wavefront of radius $R$ at abscissa $z$


### Phase at abscissa $z$

- Constant phase on sphere
- Phase  $\propto d$ ,  $r \ll R$
- $(R - d)^2 + r^2 = R^2$

### Gaussian ansatz

$$\bullet u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$

### $R$ radius spherical wavefront



## Spherical wavefront of radius $R$ at abscissa $z$


### Phase at abscissa $z$

- Constant phase on sphere
- Phase  $\propto d$ ,  $r \ll R$
- $d = R - \sqrt{R^2 - r^2}$

### Gaussian ansatz

$$\bullet u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$

### $R$ radius spherical wavefront



## Spherical wavefront of radius $R$ at abscissa $z$


### Phase at abscissa $z$

- Constant phase on sphere
- Phase  $\propto d$ ,  $r \ll R$
- $d = R - \sqrt{R^2 - r^2}$
- $d = R \left( 1 - \sqrt{1 - \frac{r^2}{R^2}} \right)$

### Gaussian ansatz

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{w(z)^2}}$$

### $R$ radius spherical wavefront



## Spherical wavefront of radius $R$ at abscissa $z$


### Phase at abscissa $z$

- Constant phase on sphere
- Phase  $\propto d$ ,  $r \ll R$
- $d = R - \sqrt{R^2 - r^2}$
- $d \approx \frac{r^2}{2R}$

### Gaussian ansatz

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$

### $R$ radius spherical wavefront



## Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and  $q' = 1$

### A quick summary

- Ansatz :  $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius :  $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation :  $q' = 1$

Assuming a plane wavefront for  $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$

# Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and  $q' = 1$

## A quick summary

- Ansatz :  $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius :  $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation :  $q(z) = q(0) + z$

Assuming a plane wavefront for  $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$

- $W^2(z) = W_0^2 \left[ 1 + \left( \frac{z}{z_R} \right)^2 \right]$

- $R(z) = z \left[ 1 + \left( \frac{z}{z_R} \right)^2 \right]$

# Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and  $q' = 1$

## A quick summary

- Ansatz :  $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius :  $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation :  $q(z) = q(0) + z$

## Assuming a plane wavefront for $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$
- $W^2(z) = W_0^2 \left[ 1 + \left( \frac{\lambda z}{\pi W_0^2} \right)^2 \right]$
- $R(z) = z \left[ 1 + \left( \frac{\pi W_0^2}{\lambda z} \right)^2 \right]$

## Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and  $q' = 1$

### A quick summary

- Ansatz :  $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius :  $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation :  $q(z) = q(0) + z$



### Assuming a plane wavefront for $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$
- $W^2(z) = W_0^2 \left[ 1 + \left( \frac{\lambda z}{\pi W_0^2} \right)^2 \right]$
- $R(z) = z \left[ 1 + \left( \frac{\pi W_0^2}{\lambda z} \right)^2 \right]$





## Gaussian Beam Intensity

$$W^2(z) = W_0^2 \left[ 1 + \left( \frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$



## Gaussian Beam Intensity


$$W^2(z) = W_0^2 \left[ 1 + \left( \frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$



$W_0$  : Beam Waist

## Gaussian Beam Intensity

$$W^2(z) = W_0^2 \left[ 1 + \left( \frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$




### Asymptotes

- $\frac{\lambda z}{\pi W_0^2} \gg 1 \Rightarrow W(z) \approx \frac{\lambda z}{\pi W_0}$
- $\gamma = \frac{\lambda}{\pi W_0}$

$W_0$  : Beam Waist

## Gaussian Beam Intensity

$$W^2(z) = W_0^2 \left[ 1 + \left( \frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$



### Asymptotes

- $\frac{\lambda z}{\pi W_0^2} \gg 1 \Rightarrow W(z) \approx \frac{\lambda z}{\pi W_0}$
- $\gamma = \frac{\lambda}{\pi W_0}$


$W_0$  : Beam Waist

## Gaussian wavefront curvature

$$R(z) = z \left[ 1 + \left( \frac{\pi W_0^2}{\lambda z} \right)^2 \right]$$

### Plane and spherical limits

- For small  $z$  :  $R = \infty$   
plane wavefront
- For high  $z$  :  $R \approx z$   
spherical wavefront



## The Rayleigh length

A quantitative criterion to decide whether a Gaussian beam is plane or spherical

Plane for small  $z$

$$\frac{\lambda z}{\pi W_0^2} \ll 1$$

- $W(z) \approx W_0$
- $\lim_{z \rightarrow 0} R(z) = \infty$


Spherical for high  $z$

$$\frac{\lambda z}{\pi W_0^2} \gg 1$$

- $W(z) \approx \frac{\lambda z}{\pi W_0}$
- $R(z) \approx z$

The Rayleigh length is the limit

$$L_R = \frac{\pi W_0^2}{\lambda}$$



# The Rayleigh length

A quantitative criterion to decide whether a Gaussian beam is plane or spherical

Plane for small  $z$

$$\frac{\lambda z}{\pi W_0^2} \ll 1$$

- $W(z) \approx W_0$
- $\lim_{z \rightarrow 0} R(z) = \infty$


Spherical for high  $z$

$$\frac{\lambda z}{\pi W_0^2} \gg 1$$

- $W(z) \approx \frac{\lambda z}{\pi W_0}$
- $R(z) \approx z$

The Rayleigh length is the limit

$$L_R = \frac{\pi W_0^2}{\lambda}$$



## The homogeneous phase shift

$P(z)$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$\Leftrightarrow$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(1 - i\frac{z}{L_R}\right)$$

Complex phase meaning



## The homogeneous phase shift

$P(z)$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$\Leftrightarrow$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(1 - i\frac{z}{L_R}\right)$$

Complex phase meaning

## The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$\Leftrightarrow$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(\sqrt{1 + \frac{z^2}{L_R^2}}\right) - i \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

## The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$\Leftrightarrow$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(\frac{W(z)}{W_0}\right) - i \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

• Real part: Phase shift with respect to plane wave

• Imaginary part: Logarithm of Gaussian beam radius

## The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$\Leftrightarrow$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$P(z) = i \ln\left(\frac{W_0}{W(z)}\right) - \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

- Real part: Phase shift with respect to plane wave
- Imaginary part:  $\frac{W_0}{W(z)}$  factor to ensure energy conservation

## The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$\Leftrightarrow$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$P(z) = i \ln\left(\frac{W_0}{W(z)}\right) - \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

- Real part : Phase shift with respect to plane wave
- Imaginary part:  $\frac{W_0}{W(z)}$  factor to ensure energy conservation

## The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$\Leftrightarrow$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$P(z) = i \ln\left(\frac{W_0}{W(z)}\right) - \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

- Real part : Phase shift with respect to plane wave
- Imaginary part:  $\frac{W_0}{W(z)}$  factor to ensure energy conservation

## The fundamental Gaussian mode

### General expression

$$E(r, z) = \frac{W_0}{W(z)} e^{-i[kz + P(z)] - r^2 \left( \frac{1}{W(z)^2} + i \frac{k}{2R(z)} \right)}$$

With, in (nearly) the order of appearance on the screen

- $W^2(z) = W_0^2 \left[ 1 + \left( \frac{z}{L_R} \right)^2 \right]$
- $R(z) = z \left[ 1 + \left( \frac{L_R}{z} \right)^2 \right]$
- $P(z) = -\tan^{-1} \left( \frac{z}{L_R} \right)$
- Rayleigh length  $L_R = \frac{\pi W_0^2}{\lambda}$
- Diffraction half angle:  $\gamma \approx \frac{\lambda}{\pi W_0} = \frac{W_0}{L_R}$

- 1 Fundamentals of Gaussian beam propagation
  - Gaussian beams vs. plane waves
  - The fundamental mode
  - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
  - Linear algebra for geometrical optics
  - A few simple matrices
  - Matrix method for Gaussian beams



# High order Hermite-Gaussian modes

A Cartesian family of higher order modes

Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

Plugged into the wave equation

$$\bullet \quad q' = 1$$

$$\bullet \quad \exists m \in \mathbb{N}, \quad \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\bullet \quad \exists n \in \mathbb{N}, \quad \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$$

# High order Hermite-Gaussian modes

A Cartesian family of higher order modes

## Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

## Plugged into the wave equation

- $q' = 1$
- $\exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$
- $qP' + (1 + m + n)j = 0$

# High order Hermite-Gaussian modes

A Cartesian family of higher order modes

## Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

## Plugged into the wave equation

- $q' = 1$
- $\exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$
- $qP' + (1 + m + n)j = 0$

# High order Hermite-Gaussian modes

A Cartesian family of higher order modes

## Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

## Plugged into the wave equation

- $q' = 1$
- $\exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$
- $qP' + (1 + m + n)j = 0$

## Behavior of Hermite-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

- Same equation for  $q$  as in the fundamental mode
- $W(z)$  and  $R(z)$  retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$\frac{\partial^2 g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\frac{\partial^2 h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$$

- Solutions are, by definition, the orthogonal Hermite polynomials
- $\mathcal{H}_0 = 1$ ,  $\mathcal{H}_1 = x$ ,  $\mathcal{H}_2 = 4x^2 - 1$ ,  $\mathcal{H}_3 = 8x^3 - 12x \dots$
- $\mathcal{H}_n$  has degree  $n$
- $g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) = \mathcal{H}_m\left(\sqrt{2}\frac{x}{W(z)}\right) \mathcal{H}_n\left(\sqrt{2}\frac{y}{W(z)}\right)$

## Behavior of Hermite-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

- Same equation for  $q$  as in the fundamental mode
- $W(z)$  and  $R(z)$  retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged



$$\frac{\partial^2 g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$$

- Solutions are, by definition, the orthogonal Hermite polynomials
- $\mathcal{H}_0 = 1$ ,  $\mathcal{H}_1 = x$ ,  $\mathcal{H}_2 = 4x^2 - 1$ ,  $\mathcal{H}_3 = 8x^3 - 12x \dots$
- $\mathcal{H}_n$  has degree  $n$
- $g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) = \mathcal{H}_m\left(\sqrt{2}\frac{x}{W(z)}\right) \mathcal{H}_n\left(\sqrt{2}\frac{y}{W(z)}\right)$

## Intensity profiles of Hermite Gaussian (HG) modes

The intensity is proportional to the squared envelope



# High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + l\phi\right)}$$

Plugged into the wave equation

$$\bullet q' = 1$$

$$\bullet \exists (l, \mu) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{\partial r} + \mu g = 0$$

$$\bullet \mu^2 = l(l+2x+1)g = 0$$



# High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g \left( \frac{r}{W(z)} \right) e^{-i \left( P(z) + \frac{k}{2q(z)} r^2 + l\phi \right)}$$

Plugged into the wave equation

- $q' = 1$
- $\exists (l, p) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{\partial x} + pg = 0$
- $qP' + (1+2p+l)j = 0$

# High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

## Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + l\phi\right)}$$

## Plugged into the wave equation

- $q' = 1$
- $\exists (l, p) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{\partial x} + pg = 0$
- $qP' + (1+2p+l)j = 0$

# High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

## Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + l\phi\right)}$$

## Plugged into the wave equation

- $q' = 1$
- $\exists (l, p) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l + 1 - x) \frac{\partial g}{\partial x} + pg = 0$
- $qP' + (1 + 2p + l)j = 0$

## Behavior of Laguerre-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

same as HG modes

- Same equation for  $q$  as in the fundamental mode
- $W(z)$  and  $R(z)$  retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{\partial x} + pg = 0$$

- Solutions are, by definition, the orthogonal generalized Laguerre polynomials
- $\mathcal{L}_0^{(l)} = 1$ ,  $\mathcal{L}_1^{(l)} = -x + l + 1$ ,  $\mathcal{L}_2^{(l)} = \frac{x^2}{2} - (l+2)x + \frac{(l+1)(l+2)}{2}$
- $\mathcal{L}_m^{(l)}$  has degree  $m$
- $g\left(\frac{r}{W(z)}\right) = \left(\sqrt{2} \frac{r}{W(z)}\right)^l \mathcal{L}_p^{(l)}\left(2 \frac{r^2}{W^2(z)}\right)$

## Behavior of Laguerre-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

same as HG modes


- Same equation for  $q$  as in the fundamental mode
- $W(z)$  and  $R(z)$  retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$r \frac{\partial^2 g}{\partial r^2} - (l + 1 - x) \frac{\partial g}{\partial x} + pg = 0$$

- Solutions are, by definition, the orthogonal generalized Laguerre polynomials
- $\mathcal{L}_0^{(l)} = 1$ ,  $\mathcal{L}_1^{(l)} = -x + l + 1$ ,  $\mathcal{L}_2^{(l)} = \frac{x^2}{2} - (l + 2)x + \frac{(l+1)(l+2)}{2}$
- $\mathcal{L}_m^{(l)}$  has degree  $m$
- $g\left(\frac{r}{W(z)}\right) = \left(\sqrt{2} \frac{r}{W(z)}\right)^l \mathcal{L}_p^{(l)}\left(2 \frac{r^2}{W^2(z)}\right)$

## Intensity profiles of Laguerre Gaussian (LG) modes

The intensity is proportional to the squared envelope



$LG(0,0)$



$LG(0,1)$  : vortex




$LG(0,2)$

## Intensity profiles of other Laguerre Gaussian (LG) modes

The intensity is proportional to the squared envelope



$LG(1,2)$



$LG(1,3)$



$LG(2,3)$

## Homogeneous phase shift is different for high order modes

$$qP' + (1 + m + n)j = 0$$

$$qP' + (1 + 2p + l)j = 0$$

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten



## Homogeneous phase shift is different for high order modes

$$qP' + (1 + m + n)j = 0$$

$$qP' + (1 + 2p + l)j = 0$$

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten

## Homogeneous phase shift is different for high order modes

$$qP' + (1 + m + n)j = 0$$

$$qP' + (1 + 2p + l)j = 0$$

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten. . . particularly in the next section

- 1 Fundamentals of Gaussian beam propagation
  - Gaussian beams vs. plane waves
  - The fundamental mode
  - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
  - Linear algebra for geometrical optics
  - A few simple matrices
  - Matrix method for Gaussian beams

# Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin **waist**: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

## Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are **seldom alone**: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

# Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- **A ray is a Poynting vector curve**
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

• Parallel rays imply a plane wavefront.

• Converging or diverging rays imply a spherical wavefront.

## Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A **bunch of rays** describes a **wavefront**

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

- Parallel rays imply a plane wavefront
- Converging or diverging rays imply a spherical wavefront

# Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

- **Parallel** rays imply a **plane wavefront**
- Converging or diverging rays imply a spherical wavefront
- But neither of them has an infinite extension !



# Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract  $\gamma = \frac{\lambda}{\pi W_0}$
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves ?

- Parallel rays imply a plane wavefront
- **Converging** or diverging rays imply a **spherical wavefront**
- But neither of them has an infinite extension !

# Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

- Parallel rays imply a plane wavefront
- Converging or diverging rays imply a spherical wavefront
- **But neither of them has an infinite extension !**

## Geometrical optic is Gaussian optics

Transversely limited plane waves

Parallel rays

Gaussian Beams **within their** Rayleigh zone

Transversely limited spherical waves

Con(Di)verging rays

Gaussian Beams **far from** their Rayleigh zone

Orders of magnitude

- He-Ne laser:  $W_0 \approx 1\text{mm}$ ,  $\lambda = 633\text{nm}$ ,  $L_R \approx 5\text{m}$
- GSM Antenna:  $W_0 \approx 1\text{m}$ ,  $\lambda \approx 33\text{cm}$ ,  $L_R \approx 10\text{m}$

## Geometrical optic is Gaussian optics

Transversely limited plane waves

Parallel rays

Gaussian Beams **within their** Rayleigh zone

Transversely limited spherical waves

Con(Di)verging rays

Gaussian Beams **far from** their Rayleigh zone

Orders of magnitude

- He-Ne laser:  $W_0 \approx 1\text{mm}$ ,  $\lambda = 633\text{nm}$ ,  $L_R \approx 5\text{m}$
- GSM Antenna:  $W_0 \approx 1\text{m}$ ,  $\lambda \approx 33\text{cm}$ ,  $L_R \approx 10\text{m}$

## Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

### Descartes made paraxial

Paraxial approximation :  $\theta \ll 1$

$$n_1 \theta_1 \approx n_2 \theta_2$$

Geometrical optics is linear algebra

- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly

## Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

### Descartes made paraxial

Paraxial approximation :  $\theta \ll 1$

$$n_1 \theta_1 \approx n_2 \theta_2$$

### Geometrical optics is linear algebra

- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly

## Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

### Descartes made paraxial

Paraxial approximation :  $\theta \ll 1$

$$n_1 \theta_1 \approx n_2 \theta_2$$

### Geometrical optics is linear algebra


- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly

## Matrix geometrical optics

A 2 dimensional linear algebra framework


The ray vector  $v = \begin{pmatrix} y \\ \theta \end{pmatrix}$

- $y$  : distance from the axis
- $\theta$  : angle to the axis



An optical system  $v' = Mv$

- $M$  is a  $2 \times 2$  real matrix
- It can describe any centered paraxial optical system






## Matrix geometrical optics

A 2 dimensional linear algebra framework

The ray vector

$$v = \begin{pmatrix} y \\ \theta \end{pmatrix}$$


- $y$  : distance from the axis
- $\theta$  : angle to the axis



An optical system

$$v' = Mv$$


- $M$  is a  $2 \times 2$  real matrix
- It can describe any centered paraxial optical system



# Optical system composition

Optical system composition reduced to matrix product

## Optical System Composition



## Matrix Composition

- $v' = M_1 \cdot v$
- $v'' = M_2 \cdot v'$
- $v'' = M_2 M_1 \cdot v$


## Complex systems

Compose simple systems

# Optical system composition

Optical system composition reduced to matrix product

## Optical System Composition



## Matrix Composition

- $v' = M_1 \cdot v$
- $v'' = M_2 \cdot v'$
- $v'' = M_2 M_1 \cdot v$


Complex systems

Compose simple systems

# Optical system composition

Optical system composition reduced to matrix product

## Optical System Composition



## Matrix Composition

- $v' = M_1 \cdot v$
- $v'' = M_2 \cdot v'$
- $v'' = M_2 M_1 \cdot v$

## Complex systems

Compose simple systems

- 1 Fundamentals of Gaussian beam propagation
  - Gaussian beams vs. plane waves
  - The fundamental mode
  - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
  - Linear algebra for geometrical optics
  - A few simple matrices
  - Matrix method for Gaussian beams

## Propagation in a homogeneous medium


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_d \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Light propagates in straight line

- No direction change:  $\theta' = \theta$
- $y' = y + d \sin(\theta)$

$M_d$

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & d \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



## Propagation in a homogeneous medium


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_d \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Light propagates in straight line

- No direction change:  $\theta' = \theta$
- $y' = y + d \sin(\theta)$

$M_d$

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & d \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



## Passing through a plane interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_p \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Descartes

- No propagation:  $y' = y$
- $n \sin(\theta) = n' \sin(\theta')$
- $\theta' \approx \frac{n}{n'} \theta$

$M_p$

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





## Passing through a plane interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_p \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Descartes

- No propagation:  $y' = y$
- $n \sin(\theta) = n' \sin(\theta')$
- $\theta' \approx \frac{n}{n'} \theta$

### $M_p$

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



## Passing through a thin lens


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_l \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Two characteristic rays

- No propagation:  $y' = y$
- Blue ray:  $y = 0 \Rightarrow \theta' = \theta$
- Red ray:  $\theta = 0 \Rightarrow \theta' = -\frac{1}{f}y$

$M_l$

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



## Passing through a thin lens


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_l \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Two characteristic rays

- No propagation:  $y' = y$
- Blue ray:  $y = 0 \Rightarrow \theta' = \theta$
- Red ray:  $\theta = 0 \Rightarrow \theta' = -\frac{1}{f}y$

$M_l$

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$




## Passing through a (thin) spherical interface

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Descartes

- Thin interface  
No propagation:  $y' = y$
- Blue ray:  $y \approx R\theta \Rightarrow \theta' = \theta$
- Red ray:  $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$



## Passing through a (thin) spherical interface

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$


### Descartes

- Thin interface  
No propagation:  $y' = y$
- Blue ray:  $y \approx R\theta \Rightarrow \theta' = \theta$
- Red ray:  $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$

$$\theta' = ay + b\theta$$

Solve for  $(a, b)$  using

- $(y, \theta') = (R\theta, \theta)$
- $(y, \theta') = (0, \frac{n}{n'}\theta)$



## Passing through a (thin) spherical interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

### Descartes

- Thin interface  
No propagation:  $y' = y$
- Blue ray:  $y \approx R\theta \Rightarrow \theta' = \theta$
- Red ray:  $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$

### $M_s$

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ \frac{n'-n}{n'R} & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$




## Mirrors

### Unfolding the light


Plane mirrors as if they did not exist

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Spherical Mirrors are thin lenses

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{2}{R} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



## Mirrors



### Unfolding the light

Plane mirrors as if they did not exist

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Spherical Mirrors are thin lenses

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{2}{R} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





## Matrix property

A determinant property stemming from all the simple matrices determinants

$n$ : start index

$n'$ : stop index

$$\forall M, \det(M) = \frac{n}{n'}$$

- 1 Fundamentals of Gaussian beam propagation
  - Gaussian beams vs. plane waves
  - The fundamental mode
  - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
  - Linear algebra for geometrical optics
  - A few simple matrices
  - Matrix method for Gaussian beams

## Gaussian modes, propagation and lenses

A Gaussian mode does not change upon propagation of by passing through thin interfaces or lenses

$$g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

- $z$  independent modulation of the fundamental mode
- Free space  $q' = 1$  common property
- Thin lens does not change mode profile

Common  $R(z)$  and  $W(z)$  behavior

All the modes share the same laws on  $q(z)$ ,  $R(z)$  and  $W(z)$

## Gaussian modes, propagation and lenses

A Gaussian mode does not change upon propagation of by passing through thin interfaces or lenses

$$g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

- $z$  independent modulation of the fundamental mode
- Free space  $q' = 1$  common property
- Thin lens does not change mode profile

### Common $R(z)$ and $W(z)$ behavior

All the modes share the same laws on  $q(z)$ ,  $R(z)$  and  $W(z)$

## Gaussian beam propagation: the ABCD law

The transformation of the complex radius  $q$  for simple optical systems

Free space

$$q' = 1$$

- $q' = q + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$

## Gaussian beam propagation: the ABCD law

The transformation of the complex radius  $q$  for simple optical systems

Free space


$$q' = 1$$

- $q' = q + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$

Plane interface


$$n/n' = R/R'$$

- $\frac{q'}{q} = \frac{n'}{n} \Rightarrow q' = \frac{1 \times q}{\frac{n'}{n}}$
- $M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{pmatrix}$



## Gaussian beam propagation: the ABCD law

The transformation of the complex radius  $q$  for simple optical systems



Thin lens

$$\frac{1}{R'} = \frac{1}{R} - \frac{1}{f}$$

- $\frac{1}{q'} = \frac{1}{q} - \frac{1}{f} \Rightarrow q' = \frac{1}{-\frac{1}{f}q + 1}$
- $M_l = \begin{pmatrix} 1 & \times q & 0 \\ -\frac{1}{f} & & 1 \end{pmatrix}$

## Gaussian beam propagation: the ABCD law

The transformation of the complex radius  $q$  for simple optical systems

Free space

$$q' = 1$$

- $q' = q + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$

Thin lens

$$\frac{1}{R'} = \frac{1}{R} - \frac{1}{f}$$

- $\frac{1}{q'} = \frac{1}{q} - \frac{1}{f} \Rightarrow q' = \frac{1}{-\frac{1}{f}q + 1}$
- $M_l = \begin{pmatrix} 1 \times q & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$

Plane interface

$$n/n' = R/R'$$

- $\frac{q'}{q} = \frac{n'}{n} \Rightarrow q' = \frac{1 \times q}{\frac{n'}{n}}$
- $M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{pmatrix}$

Kogelnik's ABCD law

$$M = \begin{pmatrix} A & B \\ C & D \end{pmatrix} \Rightarrow q' = \frac{Aq + B}{Cq + D}$$



## Gaussian beam propagation: the ABCD law

The transformation of the complex radius  $q$  for simple optical systems

Free space  $q' = 1$

- $q' = q + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$

Thin lens  $\frac{1}{R'} = \frac{1}{R} - \frac{1}{f}$

- $\frac{1}{q'} = \frac{1}{q} - \frac{1}{f} \Rightarrow q' = \frac{1}{-\frac{1}{f}q + 1}$
- $M_l = \begin{pmatrix} 1 \times q & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$

Plane interface  $n/n' = R/R'$

- $\frac{q'}{q} = \frac{n'}{n} \Rightarrow q' = \frac{1 \times q}{\frac{n'}{n}}$
- $M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{pmatrix}$

Kogelnik's ABCD law

$$M = \begin{pmatrix} A & B \\ C & D \end{pmatrix} \Rightarrow q' = \frac{Aq + B}{Cq + D}$$

Geometrical and Gaussian optics are linked through paraxial approx.

Gaussian beam propagation can be evaluated, for **any** mode, using simple matrix geometrical optics


## Focal lens example

Using the ABCD law to verify that parallel rays do converge on the focal plane

### Parallel input beam

- Input plane : just before lens
- Output plane : after length  $d$
- Input beam at waist:

$$q_0 = i \frac{\pi W_0^2}{\lambda}$$



## Focal lens example


Using the ABCD law to verify that parallel rays do converge on the focal plane

### Parallel input beam

- Input plane : just before lens
- Output plane : after length  $d$
- Input beam at waist:  $q_0 = iL_{R_0}$

### Propagation matrix

- lens:  $M_f = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$
- distance  $d$  :  $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$



## Focal lens example


Using the ABCD law to verify that parallel rays do converge on the focal plane

### Parallel input beam

- Input plane : just before lens
- Output plane : after length  $d$
- Input beam at waist:  $q_0 = iL_{R_0}$

### Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$



## Focal lens example

Using the ABCD law to verify that parallel rays do converge on the focal plane

### Parallel input beam


- Input plane : just before lens
- Output plane : after length  $d$
- Input beam at waist:  $q_0 = iL_{R_0}$

### Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$

### ABCD law

$$q_1 = \frac{df + i(f - d)L_{R_0}}{f - iL_{R_0}}$$



## Focal lens example

Using the ABCD law to verify that parallel rays do converge on the focal plane

### Parallel input beam

- Input plane : just before lens
- Output plane : after length  $d$
- Input beam at waist:  $q_0 = iL_{R0}$

### Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$

### ABCD law

$$q_1 = \frac{df + i(f - d)L_{R0}}{f - iL_{R0}}$$

$d$  for plane wavefront: imaginary  $q_1$

$$d = \frac{f}{1 + \left(\frac{f}{L_{R0}}\right)^2}$$

