

Gaussian Beams

Nicolas Fressengeas

▶ To cite this version:

Nicolas Fressengeas. Gaussian Beams. DEA. Gaussian Beams, Université de Lorraine, 2012. cel- 00670322v2

HAL Id: cel-00670322 https://cel.hal.science/cel-00670322v2

Submitted on 7 Nov 2012 (v2), last revised 10 Dec 2012 (v3)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Gaussian Beams

N. Fressengeas


Laboratoire Matériaux Optiques, Photonique et Systèmes Unité de Recherche commune à l'Université de Lorraine et à Supélec

Download this document from http://arche.univ-lorraine.fr





Further reading [KL66, GB94]



H. KOGELNIK and T. LI. Laser beams and resonators. Appl. Opt., 5(10):1550–1567, Oct 1966.



Course Outline

- Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams





- ¶ Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams





Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a homogeneous transversal electric field
- Ponting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

- Plane waves of finite extent are often used
- Strictly speaking, they are not plane waves





Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a homogeneous transversal electric field
- Ponting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

- Plane waves of finite extent are often used
- Strictly speaking, they are not plane waves





Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a homogeneous transversal electric field
- Ponting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

- Plane waves of finite extent are often used
- Strictly speaking, they are not plane waves






Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a homogeneous transversal electric field
- Ponting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

- Plane waves of finite extent are often used
- Strictly speaking, they are not plane waves
 - To what extent can we assume they are plane waves?



Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a homogeneous transversal electric field
- Ponting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

- Plane waves of finite extent are often used
- Strictly speaking, they are not plane waves
- To what extent can we assume they are plane waves?

Gaussian beams vs. plane waves The fundamental mode Higher order modes

Plane waves, Gaussian beams... what else?

Solutions of the wave equations: one finds only those he was searching for

Solving the wave equation

$$\overrightarrow{\triangle E} = \frac{1}{c^2} \frac{\partial^2 \overrightarrow{E}}{\partial t^2}$$

- Vectorial Partial Derivatives Equations
- Solutions are numerous
- An ansatz¹ is needed to seek solutions

Gaussian beams as an *ansatz*

- We will find another family of solutions
- We never pretend to get them all



¹An ansatz is an *a priori* hypothesis on the form of the sought solution.

Gaussian beams vs. plane waves The fundamental mode Higher order modes

Plane waves, Gaussian beams... what else?

Solutions of the wave equations: one finds only those he was searching for

Solving the wave equation

$$\overrightarrow{\triangle E} = \frac{1}{c^2} \frac{\partial^2 \overrightarrow{E}}{\partial t^2}$$

- Vectorial Partial Derivatives Equations
- Solutions are numerous
- An ansatz¹ is needed to seek solutions

Gaussian beams as an ansatz

- We will find another family of solutions
- We never pretend to get them all



¹An ansatz is an *a priori* hypothesis on the form of the sought solution.

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E_0} \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z) : complex beam envelope
 - e_x unit vector
- The envelope u(x, y, z) is our new unknown





Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E}_0 \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z): complex beam envelope
 - $\overrightarrow{e_{\vee}}$ unit vector



Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E_0} \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z) : complex beam envelope
 - $\overrightarrow{e_x}$ unit vector
- The envelope u(x, y, z) is our new unknown





Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E_0} \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z): complex beam envelope
 - $\overrightarrow{e_x}$ unit vector
- The envelope u(x, y, z) is our new unknown

- Wave equation: $\overrightarrow{\Delta E} = \frac{1}{c^2} \frac{\partial^2 \overrightarrow{E}}{\partial t^2}$
- Scalar harmonic wave equation: $\triangle E + \frac{\omega^2}{c^2} E = 0$
- Envelope equation:

$$\triangle \left[u\left(x,y,z\right) e^{-ikz}\right] + k^{2}u\left(x,y,z\right) e^{-ikz} =$$



Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E_0} \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z) : complex beam envelope
 - $\overrightarrow{e_x}$ unit vector
- The envelope u(x, y, z) is our new unknown

- Wave equation: $\overrightarrow{\triangle E} = \frac{1}{c^2} \frac{\partial^2 \overrightarrow{E}}{\partial t^2}$
- Scalar harmonic wave equation: $\triangle E + k^2 E = 0$
- Envelope equation:

$$\Delta \left[u(x,y,z) e^{-ikz} \right] + k^2 u(x,y,z) e^{-ikz} = 0$$





Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E_0} \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z) : complex beam envelope
 - $\overrightarrow{e_x}$ unit vector
- The envelope u(x, y, z) is our new unknown

- Scalar harmonic wave equation: $\triangle E + k^2 E = 0$
- Envelope equation: $\frac{\partial^2 \left(ue^{-ikz}\right)}{\partial z^2} + \triangle_{\perp} ue^{-ikz} + k^2 ue^{-ikz} = 0$



Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E_0} \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z) : complex beam envelope
 - $\overrightarrow{e_x}$ unit vector
- The envelope u(x, y, z) is our new unknown

- Scalar harmonic wave equation: $\triangle E + k^2 E = 0$
- Envelope equation: $e^{-ikz} \left(\triangle u 2ik \frac{\partial u}{\partial z} \right) = 0$



Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\overrightarrow{E_0} \times e^{-i\overrightarrow{k}\cdot\overrightarrow{r}}$
- Gaussian ansatz : $u(x, y, z) \overrightarrow{e_x} \times e^{-ikz}$
 - u(x, y, z): complex beam envelope
 - $\overrightarrow{e_x}$ unit vector
- The envelope u(x, y, z) is our new unknown


- Scalar harmonic wave equation: $\triangle E + k^2 E = 0$
- Envelope equation: $\triangle u 2ik\frac{\partial u}{\partial z} = 0$



The paraxial approximation


Also known as Gauss conditions, Slow Varying Envelope...





Paraxial approximation and partial derivatives

Assuming small angles is equivalent to neglecting z derivatives







Paraxial approximation and partial derivatives

Assuming small angles is equivalent to neglecting z derivatives

Transversal variation vs. longitudinal variation








$$\frac{\partial^2}{\partial z^2} \ll \frac{\partial^2}{\partial x^2}$$

 $\triangle \approx \triangle_{\perp}$


Paraxial approximation and partial derivatives

Assuming small angles is equivalent to neglecting z derivatives

Transversal variation vs. longitudinal variation







Paraxial wave equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$



Gaussian beams vs. plane waves The fundamental mode Higher order modes

- Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams





The simplest one, though probably the more important

Wave Propagation Equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius

- Real part: phase variations
- Imaginary part: intensity variations

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

- Phase shift with respect to the plane wave
- qP' + i = 0



The simplest one, though probably the more important

Wave Propagation Equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: q' = 1

A simple ansatz

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

- Phase shift with respect to the plane wave
- qP' + i = 0



The simplest one, though probably the more important

Wave Propagation Equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius

q(z)

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: q' = 1
- Integration: q(z) = q(0) + z

A simple ansatz

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

- Phase shift with respect to the plane wave
- qP' + i = 0



The simplest one, though probably the more important

Wave Propagation Equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius

q(z)

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: q' = 1
- Integration: q(z) = q(0) + z

A simple ansatz

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

- Phase shift with respect to the plane wave
- qP' + i = 0



The simplest one, though probably the more important

Wave Propagation Equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius

q(z)

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: q'=1
- Integration: q(z) = q(0) + z

A simple ansatz

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

- Phase shift with respect to the plane wave
- qP' + i = 0



The simplest one, though probably the more important

Wave Propagation Equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius

q(z)

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: q'=1
- Integration: q(z) = q(0) + z

A simple ansatz

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

- Phase shift with respect to the plane wave
- qP' + i = 0



The simplest one, though probably the more important

Wave Propagation Equation

$$\triangle_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius

q(z)

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: q' = 1
- Integration: q(z) = q(0) + z

A simple ansatz

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

- Phase shift with respect to the plane wave
- qP' + i = 0



q(z) $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$

A closer look to the signification on a complex parameter

A complex parameter is linked to two real ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$



$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

A closer look to the signification on a complex parameter

A complex parameter is linked to two real ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The ansatz re-written

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$





q(z) $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$

A closer look to the signification on a complex parameter

A complex parameter is linked to two real ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The ansatz re-written

$$u = e^{-i\left(P(z) + k\frac{r^2}{2R(z)} - i\frac{k\lambda r^2}{2\pi W(z)^2}\right)}$$





q(z) $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$

A closer look to the signification on a complex parameter

A complex parameter is linked to two real ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The ansatz re-written

$$u = e^{-\frac{i}{N}\left(P(z) + k\frac{r^2}{2R(z)} - \frac{i}{N(z)^2}\right)}$$





The complex beam radius

q(z)

A closer look to the signification on a complex parameter


$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

A complex parameter is linked to two real ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The ansatz re-written

$$u = e^{-i(P(z)+k\frac{r^2}{2R(z)})}e^{-\frac{r^2}{W(z)^2}}$$





The complex beam radius

q(z)

A closer look to the signification on a complex parameter

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

A complex parameter is linked to two real ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The ansatz re-written


$$u = e^{-i\left(P(z) + k\frac{r^2}{2R(z)}\right)}e^{-\frac{r^2}{W(z)^2}}$$

What is R?



Phase at abscissa z

- Constant phase on sphere








Phase at abscissa z


- Constant phase on sphere
- Phase $\propto d$, $r \ll R$





Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$
- $(R d)^2 + r^2 = R^2$






Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$

•
$$d = R - \sqrt{R^2 - r^2}$$

Gaussian ansatz

•
$$u = e^{-i(P(z) + k\frac{r^2}{2R(z)})}e^{-\frac{r^2}{W(z)^2}}$$





Phase at abscissa z


- Constant phase on sphere
- Phase $\propto d$, $r \ll R$

•
$$d = R - \sqrt{R^2 - r^2}$$

$$\bullet \ d = R\left(1 - \sqrt{1 - \frac{r^2}{R^2}}\right)$$

Gaussian ansatz

$$u = e^{-i(P(z) + k\frac{r^2}{2R(z)})}e^{-\frac{r^2}{W(z)^2}}$$






Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$
- $d = R \sqrt{R^2 r^2}$
- $d \approx \frac{r^2}{2R}$

Gaussian ansatz

$$u = e^{-i\left(P(z) + k\frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$





Where the Gaussian beam amplitude is derived from the ansatz and $q^\prime=1$

A quick summary

- Ansatz : $u = e^{-i\left(\frac{P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} i \frac{\lambda}{\pi W^2}$
- Beam radius equation : q' = 1

Assuming a plane wavefront for z = 0

•
$$q(0) = i \frac{\pi W_0^2}{\lambda}$$





Where the Gaussian beam amplitude is derived from the ansatz and $q^\prime=1$

A quick summary

- Ansatz : $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} i \frac{\lambda}{\pi W^2}$
- Beam radius equation : q(z) = q(0) + z

Assuming a plane wavefront for z = 0

•
$$q(0) = i \frac{\pi W_0^2}{\lambda}$$

• $VV^-(z) = VV_0 \left[1 + \left(\frac{1}{\pi VV_0^2}\right)^2\right]$ • $R(z) = z \left[1 + \left(\frac{\pi VV_0^2}{\lambda z}\right)^2\right]$





Where the Gaussian beam amplitude is derived from the ansatz and $q^\prime=1$

A quick summary

- Ansatz : $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} i \frac{\lambda}{\pi W^2}$
- Beam radius equation : q(z) = q(0) + z

Assuming a plane wavefront for z = 0

•
$$q(0) = i \frac{\pi W_0^2}{\lambda}$$

•
$$W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$

•
$$R(z) = z \left[1 + \left(\frac{\pi W_0^2}{\lambda z} \right)^2 \right]$$



Where the Gaussian beam amplitude is derived from the ansatz and $q^\prime=1$

A quick summary

- Ansatz : $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} i \frac{\lambda}{\pi W^2}$
- Beam radius equation : q(z) = q(0) + z

Assuming a plane wavefront for z = 0


•
$$q(0) = i \frac{\pi W_0^2}{\lambda}$$


•
$$W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$

•
$$R(z) = z \left[1 + \left(\frac{\pi W_0^2}{\lambda z} \right)^2 \right]$$




$$W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$









$$W^{2}\left(z
ight)=W_{0}^{2}\left[1+\left(rac{\lambda z}{\pi W_{0}^{2}}
ight)^{2}
ight]$$







$$W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$



Asymptotes


•
$$\frac{\lambda z}{\pi W_0^2} \gg 1$$
 \Rightarrow $W(z) \approx \frac{\lambda z}{\pi W_0}$

•
$$\gamma = \frac{\lambda}{\pi W}$$

W₀: Beam Waist



$$W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$



Asymptotes

$$\bullet \ \ \tfrac{\lambda z}{\pi W_0^2} \gg 1 \quad \Rightarrow \quad W\left(z\right) \approx \tfrac{\lambda z}{\pi W_0}$$

•
$$\gamma = \frac{\lambda}{\pi W_0}$$

W₀: Beam Waist




Gaussian wavefront curvature

$$R(z) = z \left[1 + \left(\frac{\pi W_0^2}{\lambda z} \right)^2 \right]$$

Plane and spherical limits

- For small $z: R = \infty$ plane wavefront
- For high $z : R \approx z$ spherical wavefront



The Rayleigh length

A quantitative criterion to decide whether a Gaussian beam is plane or spherical

Plane for small z

$$\frac{\lambda z}{\pi W_0^2} \ll 1$$

- $W(z) \approx W_0$
- $\bullet \lim_{z\to 0} R(z) = \infty$


Spherical for high z

$$\frac{\lambda z}{\pi W_0^2} \gg 1$$

- $W(z) \approx \frac{\lambda z}{\pi W_0}$
- $R(z) \approx z$

The Rayleigh length is the limit

$$L_R = \frac{\pi W_0^2}{\lambda}$$



The Rayleigh length

A quantitative criterion to decide whether a Gaussian beam is plane or spherical

Plane for small z

$$\frac{\lambda z}{\pi W_0^2} \ll 1$$

- $W(z) \approx W_0$
- $\bullet \lim_{z\to 0}R(z)=\infty$


Spherical for high z

$$\frac{\lambda z}{\pi W_0^2} \gg 1$$

- $W(z) \approx \frac{\lambda z}{\pi W_0}$
- $R(z) \approx z$

The Rayleigh length is the limit

$$L_R = \frac{\pi W_0^2}{\lambda}$$



$u=e^{-i\left(P(z)+\frac{k}{2q(z)}r^2\right)}$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(1 - i\frac{z}{L_R}\right)$$





$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(1 - i\frac{z}{L_R}\right)$$



$$u=e^{-i\left(P(z)+\frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{\imath}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(\sqrt{1 + \frac{z^2}{L_R^2}}\right) - i \tan^{-1}\left(\frac{z}{L_R}\right)$$





$u=e^{-i\left(P(z)+\frac{k}{2q(z)}r^2\right)}$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{\imath}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(\frac{W(z)}{W_0}\right) - i \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

Real part: Phase shift with respect to plane wave





$u=e^{-i\left(P(z)+\frac{k}{2q(z)}r^2\right)}$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$P(z) = i \ln \left(\frac{W_0}{W(z)} \right) - \tan^{-1} \left(\frac{z}{L_R} \right)$$

Complex phase meaning

Real part: Phase shift with respect to plane wave

ullet Imaginary part: $rac{W_0}{W(z)}$ factor to ensure energy conservation



$u=e^{-i\left(P(z)+\frac{k}{2q(z)}r^2\right)}$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{\imath}{z + iL_R}$$

Integrate it

$$P(z) = i \ln \left(\frac{W_0}{W(z)} \right) - \tan^{-1} \left(\frac{z}{L_R} \right)$$

- Real part : Phase shift with respect to plane wave
- Imaginary part: $\frac{W_0}{W(z)}$ factor to ensure energy conservation



$$u=e^{-i\left(P(z)+\frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{\imath}{z + iL_R}$$

Integrate it

$$P(z) = i \ln \left(\frac{W_0}{W(z)} \right) - \tan^{-1} \left(\frac{z}{L_R} \right)$$

- Real part : Phase shift with respect to plane wave
- Imaginary part: $\frac{W_0}{W(z)}$ factor to ensure energy conservation



The fundamental Gaussian mode

General expression

$$E(r,z) = \frac{W_0}{W(z)} e^{-i[kz+P(z)]-r^2\left(\frac{1}{W(z)^2} + i\frac{k}{2R(z)}\right)}$$

With, in (nearly) the order of appearance on the screen

•
$$W^2(z) = W_0^2 \left[1 + \left(\frac{z}{L_R} \right)^2 \right]$$

•
$$R(z) = z \left[1 + \left(\frac{L_R}{z} \right)^2 \right]$$

•
$$P(z) = -\tan^{-1}\left(\frac{z}{L_R}\right)$$

• Rayleigh length
$$L_R = \frac{\pi W_0^2}{\lambda}$$

• Diffraction half angle: $\gamma \approx \frac{\lambda}{\pi W_0} = \frac{W_0}{L_R}$





- ¶ Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams





A Cartesian family of higher order modes

Ansatz

$$u(x,y,z) = g\left(\frac{x}{W(z)}\right)h\left(\frac{y}{W(z)}\right)e^{-i\left(P(z) + \frac{k}{2q(z)}\left(x^2 + y^2\right)\right)}$$

•
$$q' = 1$$

$$\bullet \exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\bullet \exists n \in \mathbb{N}, \frac{\partial n}{\partial x^2} - 2y \frac{\partial n}{\partial x} + 2nh = 0$$





A Cartesian family of higher order modes

Ansatz

$$u(x,y,z) = g\left(\frac{x}{W(z)}\right)h\left(\frac{y}{W(z)}\right)e^{-i\left(P(z) + \frac{k}{2q(z)}\left(x^2 + y^2\right)\right)}$$

•
$$q' = 1$$

•
$$\exists m \in \mathbb{N}, \ \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\bullet \ \exists n \in \mathbb{N}, \ \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{y} + 2nh = 0$$

•
$$qP' + (1 + m + n)j = 0$$

A Cartesian family of higher order modes

Ansatz

$$u(x,y,z) = g\left(\frac{x}{W(z)}\right)h\left(\frac{y}{W(z)}\right)e^{-i\left(P(z) + \frac{k}{2q(z)}\left(x^2 + y^2\right)\right)}$$

- q' = 1
- $\exists m \in \mathbb{N}, \ \frac{\partial g}{\partial x^2} 2x \frac{\partial g}{x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \ \frac{\partial h}{\partial y^2} 2y \frac{\partial h}{y} + 2nh = 0$
- qP' + (1 + m + n)j = 0



A Cartesian family of higher order modes

Ansatz

$$u(x,y,z) = g\left(\frac{x}{W(z)}\right)h\left(\frac{y}{W(z)}\right)e^{-i\left(P(z) + \frac{k}{2q(z)}\left(x^2 + y^2\right)\right)}$$

- q' = 1
- $\exists m \in \mathbb{N}, \ \frac{\partial g}{\partial x^2} 2x \frac{\partial g}{x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \ \frac{\partial h}{\partial y^2} 2y \frac{\partial h}{y} + 2nh = 0$
- qP' + (1 + m + n)j = 0



Behavior of Hermite-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q'=1$$

- ullet Same equation for q as in the fundamental mode
- W(z) and R(z) retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$\frac{\partial^2 g}{\partial x^2} - 2x \frac{\partial g}{x} + 2mg = 0$$

$$\frac{\partial h}{\partial y^2} - 2y\frac{\partial h}{y} + 2nh = 0$$

- Solutions are, by definition, the orthogonal Hermite polynomials
- $\mathcal{H}_0 = 1$, $\mathcal{H}_1 = x$, $\mathcal{H}_2 = 4x^2 1$, $\mathcal{H}_3 = 8x^3 12x$.
- \mathcal{H}_n has degree n

•
$$g\left(\frac{x}{W(z)}\right)h\left(\frac{y}{W(z)}\right) = \mathcal{H}_m\left(\sqrt{2}\frac{x}{W(z)}\right)\mathcal{H}_n\left(\sqrt{2}\frac{y}{W(z)}\right)$$





Behavior of Hermite-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q'=1$$

- ullet Same equation for q as in the fundamental mode
- W(z) and R(z) retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$\frac{\partial^2 g}{\partial x^2} - 2x \frac{\partial g}{x} + 2mg = 0$$

$$\frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{y} + 2nh = 0$$

- Solutions are, by definition, the orthogonal Hermite polynomials
- $\mathcal{H}_0 = 1$, $\mathcal{H}_1 = x$, $\mathcal{H}_2 = 4x^2 1$, $\mathcal{H}_3 = 8x^3 12x \dots$
- \mathcal{H}_n has degree n


$$\bullet \ g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) = \mathcal{H}_m\left(\sqrt{2}\frac{x}{W(z)}\right) \mathcal{H}_n\left(\sqrt{2}\frac{y}{W(z)}\right)$$





Intensity profiles of Hermite Gaussian (HG) modes

The intensity if proportional to the squared envelope



High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + I\phi\right)}$$

Plugged into the wave equation

 $0 \ q = 1$ $\sim \partial^2 \sigma$

= aP' + (1 + 2a + b) = 0



High order Laguerre-Gaussian modes

A cylindrical family of higher order modes


Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + I\phi\right)}$$

Plugged into the wave equation

•
$$q' = 1$$

•
$$\exists (l,p) \in \mathbb{N}^2, \ r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{x} + pg = 0$$





High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + I\phi\right)}$$

Plugged into the wave equation

•
$$q' = 1$$

•
$$\exists (l,p) \in \mathbb{N}^2$$
, $r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{x} + pg = 0$

•
$$qP' + (1 + 2p + 1)j = 0$$



High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + I\phi\right)}$$

Plugged into the wave equation

- q' = 1
- $\exists (l,p) \in \mathbb{N}^2$, $r \frac{\partial^2 g}{\partial r^2} (l+1-x) \frac{\partial g}{x} + pg = 0$
- qP' + (1 + 2p + I)j = 0



Behavior of Laguerre-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q'=1$$

same as HG modes

- ullet Same equation for q as in the fundamental mode
- W(z) and R(z) retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$r\frac{\partial^2 g}{\partial r^2} - (l+1-x)\frac{\partial g}{x} + pg = 0$$

- Solutions are, by definition, the orthogonal generalized Laguerre polynomials
- $\mathcal{L}_0^{(l)} = 1$, $\mathcal{L}_1^{(l)} = -x + l + 1$, $\mathcal{L}_2^{(l)} = \frac{x^2}{2} (l+2)x + \frac{(l+1)(l+2)}{2}$
- $\mathcal{L}_{m}^{(I)}$ has degree m
- $g\left(\frac{r}{W(z)}\right) = \left(\sqrt{2}\frac{r}{W(z)}\right)^{l} \mathcal{L}_{p}^{(l)}\left(2\frac{r^{2}}{W^{2}(z)}\right)^{l}$





Behavior of Laguerre-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q'=1$$

same as HG modes

- ullet Same equation for q as in the fundamental mode
- W(z) and R(z) retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$r\frac{\partial^2 g}{\partial r^2} - (l+1-x)\frac{\partial g}{x} + pg = 0$$

- Solutions are, by definition, the orthogonal generalized Laguerre polynomials
- $\mathcal{L}_0^{(I)} = 1$, $\mathcal{L}_1^{(I)} = -x + I + 1$, $\mathcal{L}_2^{(I)} = \frac{x^2}{2} (I + 2)x + \frac{(I+1)(I+2)}{2}$
- $\mathcal{L}_m^{(I)}$ has degree m
- $g\left(\frac{r}{W(z)}\right) = \left(\sqrt{2}\frac{r}{W(z)}\right)^{l} \mathcal{L}_{p}^{(l)}\left(2\frac{r^{2}}{W^{2}(z)}\right)$





Intensity profiles of Laguerre Gaussian (LG) modes

The intensity if proportional to the squared envelope



LG(0,0)



LG(0,1): vortex




LG(0,2)



Intensity profiles of other Laguerre Gaussian (LG) modes

The intensity if proportional to the squared envelope



Gaussian beams vs. plane waves The fundamental mode Higher order modes

Homogeneous phase shift is different for high order modes aP' + (1 + m + n)i = 0 aP' + (1 + 2p + l)i = 0

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten





Homogeneous phase shift is different for high order modes aP' + (1 + m + n)i = 0 aP' + (1 + 2p + l)i = 0

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten





Gaussian beams vs. plane waves The fundamental mode Higher order modes

Homogeneous phase shift is different for high order modes aP' + (1 + m + n)i = 0 aP' + (1 + 2p + l)i = 0

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten...particularly in the next section





- Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams





Where is is shown that rays are not so thin as you may think

Geometrical optics do not deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves?





 $\gamma = \frac{\lambda}{\pi M_0}$

Where is is shown that rays are not so thin as you may think

Geometrical optics do not deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves ?





 $=\frac{\lambda}{\pi W_0}$

Where is is shown that rays are not so thin as you may think

Geometrical optics do not deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves?







 $=\frac{\lambda}{\pi W_0}$

Where is is shown that rays are not so thin as you may think

Geometrical optics do not deal with thin rays

• A thin ray has a thin waist: it should diffract

- $\gamma = \frac{\lambda}{\pi W_0}$
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves ?

Parallel rays imply a plane wavefront

Converging or diverging rays imply a spherical wavefront





Where is is shown that rays are not so thin as you may think

Geometrical optics do not deal with thin rays

A thin ray has a thin waist: it should diffract

- $\gamma = \frac{\lambda}{\pi W_0}$
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves ?

- Parallel rays imply a plane wavefront
- Converging or diverging rays imply a spherical wavefron
- But neither of them has an infinite extension!



Where is is shown that rays are not so thin as you may think

Geometrical optics do not deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves?

- Parallel rays imply a plane wavefront
- Converging or diverging rays imply a spherical wavefront
- But neither of them has an infinite extension!



 $\gamma = \frac{\lambda}{\pi W_0}$

Where is is shown that rays are not so thin as you may think

Geometrical optics do not deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

Do geometrical optics deal with plane and spherical waves?

- Parallel rays imply a plane wavefront
- Converging or diverging rays imply a spherical wavefront
- But neither of them has an infinite extension!



 $\gamma = \frac{\lambda}{\pi W_0}$

Geometrical optic is Gaussian optics

Transversely limited plane waves

Parallel rays

Gaussian Beams within their Rayleigh zone

Transversely limited spherical waves

Con(Di)verging rays

Gaussian Beams far from their Rayleigh zone

Orders of magnitude

- He-Ne laser: $W_0 \approx 1 \text{mm}, \lambda = 633 \text{nm}, L_R \approx 5 \text{m}$
- GSM Antenna: $W_0 \approx 1 \text{m}, \lambda \approx 33 \text{cm}, L_R \approx 10 \text{m}$



Geometrical optic is Gaussian optics

Transversely limited plane waves

Parallel rays

Gaussian Beams within their Rayleigh zone

Transversely limited spherical waves

Con(Di)verging rays

Gaussian Beams far from their Rayleigh zone

Orders of magnitude

- He-Ne laser: $W_0 \approx 1 \mathrm{mm}, \lambda = 633 \mathrm{nm}, L_R \approx 5 \mathrm{m}$
- GSM Antenna: $W_0 \approx 1 \text{m}, \lambda \approx 33 \text{cm}, L_R \approx 10 \text{m}$

Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1\sin(\theta_1)=n_2\sin(\theta_2)$$

Descartes made paraxial

Paraxial approximation : $\theta \ll 1$

 $n_1\theta_1 \approx n_2\theta_2$

Geometrical optics is linear algebra

Straight line areas tion is linear

Straight line propagation is linear

described linearly





Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

Descartes made paraxial

Paraxial approximation : $\theta \ll 1$

 $n_1\theta_1 \approx n_2\theta_2$

Geometrical optics is linear algebra

- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly





Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

Descartes made paraxial

Paraxial approximation : $\theta \ll 1$

 $n_1\theta_1 \approx n_2\theta_2$

Geometrical optics is linear algebra

- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly





Matrix geometrical optics

A 2 dimensional linear algebra framework

The ray vector


$$v = \begin{pmatrix} y \\ \theta \end{pmatrix}$$

- y : distance from the axis
- \bullet θ : angle to the axis

An optical system



- M is a 2 \times 2 real matrix
- It can describe any centered paraxial optical system





Matrix geometrical optics

A 2 dimensional linear algebra framework

The ray vector


$$v = \begin{pmatrix} y \\ \theta \end{pmatrix}$$

- y : distance from the axis
- \bullet θ : angle to the axis

An optical system

$$v' = Mv$$


- M is a 2×2 real matrix
- It can describe any centered paraxial optical system





Optical system composition

Optical system composition reduced to matrix product



Matrix Composition

•
$$v' = M_1 \cdot v$$

•
$$v'' = M_2 \cdot v'$$

$$v'' = M_2 M_1 \cdot v$$

Complex systems


Compose simple systems





Optical system composition

Optical system composition reduced to matrix product



Matrix Composition

$$v' = M_1 \cdot v$$

•
$$v'' = M_2 \cdot v'$$

•
$$v'' = M_2 M_1 \cdot v$$

Complex systems


Compose simple systems





Optical system composition

Optical system composition reduced to matrix product



Matrix Composition

$$v' = M_1 \cdot v$$

•
$$v'' = M_2 \cdot v'$$

•
$$v'' = M_2 M_1 \cdot v$$

Complex systems

Compose simple systems



- Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams





Propagation in a homogeneous medium


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_d \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Light propagates in straight line

- No direction change: $\theta' = \theta$
- $y' = y + d \sin(\theta)$

 M_d

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & d \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





Propagation in a homogeneous medium


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_d \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Light propagates in straight line

- No direction change: $\theta' = \theta$
- $y' = y + d \sin(\theta)$

 M_d

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & d \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





Passing through a plane interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_p \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

- No propagation: y' = y
- $n \sin(\theta) = n' \sin(\theta')$
- $\theta' \approx \frac{n}{n'}\theta$

 M_p

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$







Passing through a plane interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_p \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

- No propagation: y' = y
- $n \sin(\theta) = n' \sin(\theta')$
- $\theta' \approx \frac{n}{n'}\theta$

 M_p

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





Passing through a thin lens


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_l \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Two characteristic rays

- No propagation: y' = y
- Blue ray: $y = 0 \Rightarrow \theta' = \theta$
- Red ray: $\theta = 0 \Rightarrow \theta' = -\frac{1}{f}y$

 M_I

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{1}{\epsilon} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





Passing through a thin lens


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_I \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Two characteristic rays

- No propagation: y' = y
- Blue ray: $y = 0 \Rightarrow \theta' = \theta$
- Red ray: $\theta = 0 \Rightarrow \theta' = -\frac{1}{f}y$

 M_{l}

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





Passing through a (thin) spherical interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

Thin interface

No propagation: y' = y

- Blue ray: $y \approx R\theta \Rightarrow \theta' = \theta$
- Red ray: $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$





Passing through a (thin) spherical interface

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

 Thin interface No propagation: y' = y

• Blue ray: $y \approx R\theta \Rightarrow \theta' = \theta$


• Red ray: $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$

$$\theta' = ay + b\theta$$

Solve for (a, b) using

•
$$(y, \theta') = (R\theta, \theta)$$

•
$$(y, \theta') = (0, \frac{n}{p'}\theta)$$





Passing through a (thin) spherical interface

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes


Thin interface

No propagation: y' = y

- Blue ray: $v \approx R\theta \Rightarrow \theta' = \theta$
- Red ray: $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$

 M_s

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ \frac{n'-n}{n'R} & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





Mirrors

Unfolding the light

Plane mirrors as if they did not exist

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Spherical Mirrors are thin lenses

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{2}{\mathcal{P}} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$





Mirrors


Unfolding the light


Plane mirrors as if they did not exist

$$\begin{pmatrix} \mathbf{y}' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & \mathbf{0} \\ \mathbf{0} & \mathbf{1} \end{bmatrix} \begin{pmatrix} \mathbf{y} \\ \theta \end{pmatrix}$$

Spherical Mirrors are thin lenses

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{2}{B} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$







Matrix property

A determinant property stemming from all the simple matrices determinants

$$n$$
: start index n' : stop index $\forall M$, det $(M) = \frac{n}{n'}$





- Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams



Gaussian modes, propagation and lenses

A Gaussian mode does not change upon propagation of by passing through thin interfaces or lenses

$$g\left(\frac{x}{W(z)}\right)h\left(\frac{y}{W(z)}\right)e^{-i\left(P(z)+\frac{k}{2q(z)}\left(x^2+y^2\right)\right)}$$

- z independent modulation of the fundamental mode
- Free space q' = 1 common property
- Thin lens does not change mode profile

Common R(z) and W(z) behavior

All the modes share the same laws on q(z), R(z) and W(z)



Gaussian modes, propagation and lenses

A Gaussian mode does not change upon propagation of by passing through thin interfaces or lenses

$$g\left(\frac{x}{W(z)}\right)h\left(\frac{y}{W(z)}\right)e^{-i\left(P(z)+\frac{k}{2q(z)}\left(x^2+y^2\right)\right)}$$

- z independent modulation of the fundamental mode
- Free space q' = 1 common property
- Thin lens does not change mode profile

Common R(z) and W(z) behavior

All the modes share the same laws on q(z), R(z) and W(z)

The transformation of the complex radius q for simple optical systems

Free space
$$q' = 1$$
• $q_1 = q_0 + d$
• $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$



The transformation of the complex radius q for simple optical systems

Free space

$$q'=1$$

•
$$q_1 = q_0 + d$$


•
$$M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$$

Plane interface

$$n_0/n_1 = R_0/R_1$$

•
$$\frac{q_1}{q_0} = \frac{n_1}{n_0} \Rightarrow q_1 = \frac{1 \times q_0}{\frac{n}{n'}}$$


•
$$M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n_0}{n_0} \end{pmatrix}$$







The transformation of the complex radius q for simple optical systems



Thin lens

$$\tfrac{1}{R_1} = \tfrac{1}{R_0} - \tfrac{1}{f}$$

$$\bullet$$
 $\frac{1}{q_1} = \frac{1}{q_0} - \frac{1}{f} \Rightarrow q_1 = \frac{1}{-\frac{1}{f}q_0 + 1}$

$$\bullet \ M_I = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$$



The transformation of the complex radius q for simple optical systems

Free space

$$q = q_0 + d$$

•
$$M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$$

Plane interface

$$n_0/n_1=R_0/R_1$$

$$\bullet \ \frac{q_1}{q_0} = \frac{n_1}{n_0} \Rightarrow q_1 = \frac{1 \times q_0}{\frac{n}{n'}}$$

$$\bullet \ M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n_0}{n_1} \end{pmatrix}$$

q'=1 Thin lens

$$\frac{1}{R_1} = \frac{1}{R_0} - \frac{1}{f}$$

$$\bullet \ \frac{1}{q_1} = \frac{1}{q_0} - \frac{1}{f} \Rightarrow q_1 = \frac{1}{-\frac{1}{f}q_0 + 1}$$

$$\bullet \ M_I = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$$

Kogelnik's ABCD law

$$M = \begin{pmatrix} A & B \\ C & D \end{pmatrix} \Rightarrow q_1 = \frac{Aq_0 + B}{Cq_0 + D}$$



The transformation of the complex radius q for simple optical systems

Free space

$$q' =$$

•
$$q_1 = q_0 + d$$

•
$$M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$$

Plane interface

$$n_0/n_1=R_0/R_1$$

$$\bullet \ \frac{q_1}{q_0} = \frac{n_1}{n_0} \Rightarrow q_1 = \frac{1 \times q_0}{\frac{n}{n'}}$$

•
$$M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n_0}{n_1} \end{pmatrix}$$

q'=1 Thin lens

$$\frac{1}{R_1} = \frac{1}{R_0} - \frac{1}{f}$$

$$\bullet$$
 $\frac{1}{q_1} = \frac{1}{q_0} - \frac{1}{f} \Rightarrow q_1 = \frac{1}{-\frac{1}{f}q_0 + 1}$

$$\bullet \ M_I = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$$

Kogelnik's ABCD law

$$M = \begin{pmatrix} A & B \\ C & D \end{pmatrix} \Rightarrow q_1 = \frac{Aq_0 + B}{Cq_0 + D}$$

Geometrical and Gaussian optics are linked through paraxial approx.

Gaussian beam propagation can be evaluated, for any mode, using simple matrix geometrical optics




Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam

- Input plane : just before lens
- Output plane : after length d
- Input beam at waist:

$$q_0 = i \frac{\pi W_0^2}{\lambda}$$





Using the ABCD law to verify that parallel rays do converge on the focal plane


Parallel input beam

- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R_0}$

Propagation matrix

• lens:
$$M_f = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$$

• distance
$$d: M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$$








Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam

- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R_0}$

Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$





Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam


- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R_0}$

Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$

ABCD law

$$q_1 = \frac{df + i(f - d)L_{R_0}}{f - iL_{R_0}}$$







Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam


- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R_0}$

Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$

ABCD law

$$q_1 = \frac{df + i(f - d)L_{R_0}}{f - iL_{R_0}}$$



d for plane wavefront: imaginary q_1

$$d = \frac{f}{1 + \left(\frac{f}{L_{R_0}}\right)^2}$$