



Gaussian Beams

Nicolas Fressengeas

► To cite this version:

Nicolas Fressengeas. Gaussian Beams. DEA. Gaussian Beams, Université de Lorraine, 2012. cel-00670322v3

HAL Id: cel-00670322

<https://cel.hal.science/cel-00670322v3>

Submitted on 10 Dec 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Gaussian Beams

N. Fressengeas

Laboratoire Matériaux Optiques, Photonique et Systèmes
Unité de Recherche commune à l'Université de Lorraine et à Supélec

Download this document from
<http://arche.univ-lorraine.fr>



Further reading

[KL66, GB94]



A. Gerrard and J.M. Burch.

Introduction to matrix methods in optics.

Dover, 1994.



H. KOGELNIK and T. LI.

Laser beams and resonators.

Appl. Opt., 5(10):1550–1567, Oct 1966.



Course Outline

- 1 Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams



1 Fundamentals of Gaussian beam propagation

- Gaussian beams vs. plane waves
- The fundamental mode
- Higher order modes

2 Matrix methods for geometrical and Gaussian optics

- Linear algebra for geometrical optics
- A few simple matrices
- Matrix method for Gaussian beams



Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves



Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and **power density**, are also homogeneous
- Total carried power is infinite

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves

But in practice, we can assume they are plane waves



Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- **Total carried power is infinite**

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves
- To what extent can we assume they are plane waves ?



Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves
- To what extent can we assume they are plane waves ?



Plane waves do not exist

Waves carrying an infinite amount of energy cannot come into existence

Planes waves

- Plane wave have a **homogeneous** transversal electric field
- Poynting's vector norm, and power density, are also homogeneous
- Total carried power is infinite

Practical use of plane wave theory: usual unsaid approximation

- Plane waves of **finite extent** are often used
- Strictly speaking, they are **not** plane waves
- **To what extent can we assume they are plane waves ?**



Plane waves, Gaussian beams. . . what else ?

Solutions of the wave equations: one finds only those he was searching for

Solving the wave equation

$$\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$$

- Vectorial Partial Derivatives Equations
- Solutions are numerous
- An **ansatz**¹ is needed to seek solutions

Gaussian beams as an *ansatz*

- We will find another family of solutions
- We never pretend to get them all

¹An ansatz is an *a priori* hypothesis on the form of the sought solution.



Plane waves, Gaussian beams. . . what else ?

Solutions of the wave equations: one finds only those he was searching for

Solving the wave equation

$$\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$$

- Vectorial Partial Derivatives Equations
- Solutions are numerous
- An **ansatz**¹ is needed to seek solutions

Gaussian beams as an *ansatz*

- We will find another **family of solutions**
- We never pretend to get them all

¹An ansatz is an *a priori* hypothesis on the form of the sought solution.



Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our new unknown

Envelope equation



Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our new unknown

Envelope equation

- Wave equation: $\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation: $\Delta E + E = 0$



Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our **new unknown**

Envelope equation

- Wave equation: $\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation: $\Delta E + E = 0$
- Envelope equation:
 $[\Delta u(x, y, z) e^{ikz}] + k^2 u(x, y, z) e^{ikz} = 0$



Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our **new unknown**

Envelope equation

- Wave equation: $\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation: $\Delta E + \frac{\omega^2}{c^2} E = 0$
- Envelope equation:
 $\Delta [u(x, y, z) e^{-ikz}] + k^2 u(x, y, z) e^{-ikz} = 0$

Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our **new unknown**

Envelope equation

- Wave equation: $\Delta \vec{E} = \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2}$
- Scalar harmonic wave equation: $\Delta E + k^2 E = 0$
- Envelope equation:
 $\Delta [u(x, y, z) e^{-ikz}] + k^2 u(x, y, z) e^{-ikz} = 0$

Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our **new unknown**

Envelope equation

- Scalar harmonic wave equation: $\Delta E + k^2 E = 0$
- Envelope equation: $\frac{\partial^2 (u e^{-ikz})}{\partial z^2} + \Delta_{\perp} u e^{-ikz} + k^2 u e^{-ikz} = 0$



Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our **new unknown**

Envelope equation

- Scalar harmonic wave equation: $\Delta E + k^2 E = 0$
- Envelope equation: $e^{-ikz} (\Delta u - 2ik \frac{\partial u}{\partial z}) = 0$



Gaussian *ansatz*

Plugging the ansatz into the wave equation builds the envelope equation

Introducing a space dependent envelope

- Plane wave: $\vec{E}_0 \times e^{-i\vec{k} \cdot \vec{r}}$
- Gaussian ansatz : $u(x, y, z) \vec{e}_x \times e^{-ikz}$
 - $u(x, y, z)$: **complex** beam envelope
 - \vec{e}_x unit vector
- The envelope $u(x, y, z)$ is our **new unknown**

Envelope equation

- Scalar harmonic wave equation: $\Delta E + k^2 E = 0$
- Envelope equation: $\Delta u - 2ik \frac{\partial u}{\partial z} = 0$




The paraxial approximation

Also known as Gauss conditions, Slow Varying Envelope. . .

Non Paraxial Beam



Paraxial Beam




Paraxial approximation and partial derivatives


Assuming small angles is equivalent to neglecting z derivatives

Transversal variation vs. longitudinal variation

Non Paraxial Beam



Paraxial Beam




Paraxial approximation and partial derivatives


Assuming small angles is equivalent to neglecting z derivatives

Transversal variation vs. longitudinal variation

Non Paraxial Beam



Paraxial Beam



Transversal Laplacian

$$\frac{\partial^2}{\partial z^2} \ll \frac{\partial^2}{\partial x^2}$$


$$\Delta \approx \Delta_{\perp}$$

Paraxial approximation and partial derivatives


Assuming small angles is equivalent to neglecting z derivatives

Transversal variation vs. longitudinal variation

Non Paraxial Beam



Paraxial Beam



Paraxial wave equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$



- 1 Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams



A first solution to the paraxial wave equation

The simplest one, though probably the more important

Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations

- Focusing strength $q = i$
- Inversion $q(z) = q(0) + z$

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

Phase shift $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$



A first solution to the paraxial wave equation

The simplest one, though probably the more important

Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: $q' = 1/q$
- Integration: $q(z) = q(0) + z$

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$



A first solution to the paraxial wave equation

The simplest one, though probably the more important

Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: $q' = 1$
- Integration: $q(z) = q(0) + z$

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

Phase shift

$P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$



A first solution to the paraxial wave equation

The simplest one, though probably the more important

Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: $q' = 1$
- Integration: $q(z) = q(0) + z$

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

Phase shift

$P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$



A first solution to the paraxial wave equation

The simplest one, though probably the more important

Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: $q' = 1$
- Integration: $q(z) = q(0) + z$

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift

$P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$



A first solution to the paraxial wave equation

The simplest one, though probably the more important

Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: $q' = 1$
- Integration: $q(z) = q(0) + z$

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift $P(z)$

- Phase shift **with respect** to the plane wave
- $qP' + i = 0$



A first solution to the paraxial wave equation

The simplest one, though probably the more important

Wave Propagation Equation

$$\Delta_{\perp} u - 2ik \frac{\partial u}{\partial z} = 0$$

Complex beam radius $q(z)$

- Real part: phase variations
- Imaginary part: intensity variations
- Plugging ansatz: $q' = 1$
- Integration: $q(z) = q(0) + z$

A simple *ansatz*

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Phase shift $P(z)$

- Phase shift with respect to the plane wave
- $qP' + i = 0$



The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$



The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$



The complex beam radius

$$q(z)$$

A closer look to the signification on a complex parameter

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)} - i \frac{k\lambda r^2}{2\pi W(z)^2}\right)}$$



The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)} - i \frac{r^2}{W(z)^2}\right)}$$



The complex beam radius

$$q(z)$$

A closer look to the signification on a complex parameter


$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$



The complex beam radius

A closer look to the signification on a complex parameter

$$q(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)} r^2\right)}$$

A **complex** parameter is linked to two **real** ones

$$\frac{1}{q} = \frac{1}{R} - i \frac{\lambda}{\pi W^2}$$

The *ansatz* re-written

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$

What is R ?



Spherical wavefront of radius R at abscissa z


Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$

Gaussian ansatz

- $u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$

R radius spherical wavefront



Spherical wavefront of radius R at abscissa z


Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$

Gaussian ansatz

- $u = e^{-i\left(P(z)+k\frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$

R radius spherical wavefront



Spherical wavefront of radius R at abscissa z


Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$
- $(R - d)^2 + r^2 = R^2$

Gaussian ansatz

- $u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$

R radius spherical wavefront



Spherical wavefront of radius R at abscissa z


Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$
- $d = R - \sqrt{R^2 - r^2}$

Gaussian ansatz

- $u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$

R radius spherical wavefront



Spherical wavefront of radius R at abscissa z


Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$
- $d = R - \sqrt{R^2 - r^2}$
- $d = R \left(1 - \sqrt{1 - \frac{r^2}{R^2}} \right)$

Gaussian ansatz

$$u = e^{-i \left(P(z) + k \frac{r^2}{2R(z)} \right)} e^{-\frac{r^2}{w(z)^2}}$$

R radius spherical wavefront



Spherical wavefront of radius R at abscissa z


Phase at abscissa z

- Constant phase on sphere
- Phase $\propto d$, $r \ll R$
- $d = R - \sqrt{R^2 - r^2}$
- $d \approx \frac{r^2}{2R}$

Gaussian ansatz

$$u = e^{-i\left(P(z) + k \frac{r^2}{2R(z)}\right)} e^{-\frac{r^2}{W(z)^2}}$$

R radius spherical wavefront



Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and $q' = 1$

A quick summary

- Ansatz : $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation : $q' = 1$

Assuming a plane wavefront for $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$



Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and $q' = 1$

A quick summary

- Ansatz : $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation : $q(z) = q(0) + z$

Assuming a plane wavefront for $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$
- $W^2(z) = W_0^2 \left[1 + \left(\frac{z}{z_R} \right)^2 \right]$
- $R(z) = z \left[1 + \left(\frac{z}{z_R} \right)^2 \right]$



Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and $q' = 1$

A quick summary

- Ansatz : $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation : $q(z) = q(0) + z$

Assuming a plane wavefront for $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$
- $W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$
- $R(z) = z \left[1 + \left(\frac{\pi W_0^2}{\lambda z} \right)^2 \right]$



Gaussian Beam Complex Amplitude

Where the Gaussian beam amplitude is derived from the ansatz and $q' = 1$

A quick summary



- Ansatz : $u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$
- Complex beam radius : $\frac{1}{q} = \frac{1}{R} - i\frac{\lambda}{\pi W^2}$
- Beam radius equation : $q(z) = q(0) + z$

Assuming a plane wavefront for $z = 0$

- $q(0) = i\frac{\pi W_0^2}{\lambda}$
- $W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2}\right)^2\right]$
- $R(z) = z \left[1 + \left(\frac{\pi W_0^2}{\lambda z}\right)^2\right]$



Gaussian Beam Intensity

$$w^2(z) = w_0^2 \left[1 + \left(\frac{\lambda z}{\pi w_0^2} \right)^2 \right]$$




Gaussian Beam Intensity

$$w^2(z) = w_0^2 \left[1 + \left(\frac{\lambda z}{\pi w_0^2} \right)^2 \right]$$



Gaussian Beam Intensity

$$W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$



Asymptotes


- $\frac{\lambda z}{\pi W_0^2} \gg 1 \Rightarrow W(z) \approx \frac{\lambda z}{\pi W_0}$
- $\gamma = \frac{\lambda}{\pi W_0}$

W_0 : Beam Waist



Gaussian Beam Intensity

$$W^2(z) = W_0^2 \left[1 + \left(\frac{\lambda z}{\pi W_0^2} \right)^2 \right]$$



Asymptotes

- $\frac{\lambda z}{\pi W_0^2} \gg 1 \Rightarrow W(z) \approx \frac{\lambda z}{\pi W_0}$
- $\gamma = \frac{\lambda}{\pi W_0}$

W_0 : Beam Waist




Gaussian wavefront curvature

$$R(z) = z \left[1 + \left(\frac{\pi W_0^2}{\lambda z} \right)^2 \right]$$

Plane and spherical limits

- For small z : $R = \infty$
plane wavefront
- For high z : $R \approx z$
spherical wavefront



The Rayleigh length

A quantitative criterion to decide whether a Gaussian beam is plane or spherical

Plane for small z $\frac{\lambda z}{\pi W_0^2} \ll 1$


- $W(z) \approx W_0$
- $\lim_{z \rightarrow 0} R(z) = \infty$

Spherical for high z $\frac{\lambda z}{\pi W_0^2} \gg 1$

- $W(z) \approx \frac{\lambda z}{\pi W_0}$
- $R(z) \approx z$

The Rayleigh length is the limit

$$L_R = \frac{\pi W_0^2}{\lambda}$$



The Rayleigh length

A quantitative criterion to decide whether a Gaussian beam is plane or spherical

Plane for small z $\frac{\lambda z}{\pi W_0^2} \ll 1$


- $W(z) \approx W_0$
- $\lim_{z \rightarrow 0} R(z) = \infty$

Spherical for high z $\frac{\lambda z}{\pi W_0^2} \gg 1$

- $W(z) \approx \frac{\lambda z}{\pi W_0}$
- $R(z) \approx z$

The Rayleigh length is the limit

$$L_R = \frac{\pi W_0^2}{\lambda}$$



The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

\Leftrightarrow

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(1 - i\frac{z}{L_R}\right)$$

Complex phase meaning



The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(1 - i\frac{z}{L_R}\right)$$

Complex phase meaning



The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

$$\Leftrightarrow$$

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(\sqrt{1 + \frac{z^2}{L_R^2}}\right) - i \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning



The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

\Leftrightarrow

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$iP(z) = \ln\left(\frac{W(z)}{W_0}\right) - i \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

• Real part: Phase shift with respect to plane wave

• Imaginary part: $\frac{1}{2} \ln\left(\frac{W(z)}{W_0}\right)$ factor to ensure energy conservation



The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0$$

\Leftrightarrow

$$P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$P(z) = i \ln \left(\frac{W_0}{W(z)} \right) - \tan^{-1} \left(\frac{z}{L_R} \right)$$

Complex phase meaning

- Real part: Phase shift with respect to plane wave
- Imaginary part: $\frac{W_0}{W(z)}$ factor to ensure energy conservation



The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0 \quad \Leftrightarrow \quad P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$P(z) = i \ln \left(\frac{W_0}{W(z)} \right) - \tan^{-1} \left(\frac{z}{L_R} \right)$$

Complex phase meaning

- Real part : Phase shift with respect to plane wave
- Imaginary part: $\frac{W_0}{W(z)}$ factor to ensure energy conservation



The homogeneous phase shift

$$P(z)$$

$$u = e^{-i\left(P(z) + \frac{k}{2q(z)}r^2\right)}$$

Recall the equation

$$qP' + i = 0 \quad \Leftrightarrow \quad P'(z) = -\frac{i}{z + iL_R}$$

Integrate it

$$P(z) = i \ln\left(\frac{W_0}{W(z)}\right) - \tan^{-1}\left(\frac{z}{L_R}\right)$$

Complex phase meaning

- Real part : Phase shift with respect to plane wave
- Imaginary part: $\frac{W_0}{W(z)}$ factor to ensure energy conservation



The fundamental Gaussian mode

General expression

$$E(r, z) = \frac{W_0}{W(z)} e^{-i[kz + P(z)] - r^2 \left(\frac{1}{W(z)^2} + i \frac{k}{2R(z)} \right)}$$

With, in (nearly) the order of appearance on the screen

- $W^2(z) = W_0^2 \left[1 + \left(\frac{z}{L_R} \right)^2 \right]$
- $R(z) = z \left[1 + \left(\frac{L_R}{z} \right)^2 \right]$
- $P(z) = -\tan^{-1} \left(\frac{z}{L_R} \right)$
- Rayleigh length $L_R = \frac{\pi W_0^2}{\lambda}$
- Diffraction half angle: $\gamma \approx \frac{\lambda}{\pi W_0} = \frac{W_0}{L_R}$



1 Fundamentals of Gaussian beam propagation

- Gaussian beams vs. plane waves
- The fundamental mode
- Higher order modes

2 Matrix methods for geometrical and Gaussian optics

- Linear algebra for geometrical optics
- A few simple matrices
- Matrix method for Gaussian beams



High order Hermite-Gaussian modes

A Cartesian family of higher order modes

Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

Plugged into the wave equation

$$\bullet q' = 1$$

$$\bullet \exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\bullet \exists n \in \mathbb{N}, \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$$

$$\bullet \frac{P'(z)}{2} + \frac{k}{q(z)} = 0$$



High order Hermite-Gaussian modes

A Cartesian family of higher order modes

Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

Plugged into the wave equation

- $q' = 1$
- $\exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$
- $qP' + (1 + m + n)j = 0$



High order Hermite-Gaussian modes

A Cartesian family of higher order modes

Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

Plugged into the wave equation

- $q' = 1$
- $\exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$
- $qP' + (1 + m + n)j = 0$



High order Hermite-Gaussian modes

A Cartesian family of higher order modes

Ansatz

$$u(x, y, z) = g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

Plugged into the wave equation

- $q' = 1$
- $\exists m \in \mathbb{N}, \frac{\partial g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$
- $\exists n \in \mathbb{N}, \frac{\partial h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$
- $qP' + (1 + m + n)j = 0$



Behavior of Hermite-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

- Same equation for q as in the fundamental mode
- $W(z)$ and $R(z)$ retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$\frac{\partial^2 g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\frac{\partial^2 h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$$

- Solutions are, by definition, the orthogonal Hermite polynomials
- $\mathcal{H}_0 = 1$, $\mathcal{H}_1 = x$, $\mathcal{H}_2 = 4x^2 - 1$, $\mathcal{H}_3 = 8x^3 - 12x \dots$
- \mathcal{H}_n has degree n
- $g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) = \mathcal{H}_m\left(\sqrt{2}\frac{x}{W(z)}\right) \mathcal{H}_n\left(\sqrt{2}\frac{y}{W(z)}\right)$



Behavior of Hermite-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

- Same equation for q as in the fundamental mode
- $W(z)$ and $R(z)$ retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged





$$\frac{\partial^2 g}{\partial x^2} - 2x \frac{\partial g}{\partial x} + 2mg = 0$$

$$\frac{\partial^2 h}{\partial y^2} - 2y \frac{\partial h}{\partial y} + 2nh = 0$$

- Solutions are, by definition, the orthogonal Hermite polynomials
- $\mathcal{H}_0 = 1$, $\mathcal{H}_1 = x$, $\mathcal{H}_2 = 4x^2 - 1$, $\mathcal{H}_3 = 8x^3 - 12x \dots$
- \mathcal{H}_n has degree n
- $g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) = \mathcal{H}_m\left(\sqrt{2}\frac{x}{W(z)}\right) \mathcal{H}_n\left(\sqrt{2}\frac{y}{W(z)}\right)$

Intensity profiles of Hermite Gaussian (HG) modes

The intensity is proportional to the squared envelope



High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)} r^2 + l\phi\right)}$$

Plugged into the wave equation

$$\bullet q' = 1$$

$$\bullet \exists (l, p) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{\partial x} + p g = 0$$

$$\bullet r^2 \frac{\partial^2 g}{\partial r^2} + (2+2p+2l) g = 0$$



High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + l\phi\right)}$$

Plugged into the wave equation

- $q' = 1$
- $\exists (l, p) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l + 1 - x) \frac{\partial g}{\partial x} + pg = 0$
- $qP' + (1 + 2p + l)j = 0$



High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + l\phi\right)}$$

Plugged into the wave equation

- $q' = 1$
- $\exists (l, p) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l + 1 - x) \frac{\partial g}{\partial x} + pg = 0$
- $qP' + (1 + 2p + l)j = 0$



High order Laguerre-Gaussian modes

A cylindrical family of higher order modes

Ansatz

$$u(r, \phi, z) = g\left(\frac{r}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}r^2 + l\phi\right)}$$

Plugged into the wave equation

- $q' = 1$
- $\exists (l, p) \in \mathbb{N}^2, r \frac{\partial^2 g}{\partial r^2} - (l + 1 - x) \frac{\partial g}{\partial x} + pg = 0$
- $qP' + (1 + 2p + l)j = 0$



Behavior of Laguerre-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

same as HG modes

- Same equation for q as in the fundamental mode
- $W(z)$ and $R(z)$ retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$r \frac{\partial^2 g}{\partial r^2} - (l+1-x) \frac{\partial g}{\partial x} + pg = 0$$

- Solutions are, by definition, the orthogonal generalized Laguerre polynomials
- $\mathcal{L}_0^{(l)} = 1$, $\mathcal{L}_1^{(l)} = -x + l + 1$, $\mathcal{L}_2^{(l)} = \frac{x^2}{2} - (l+2)x + \frac{(l+1)(l+2)}{2}$
- $\mathcal{L}_m^{(l)}$ has degree m
- $g\left(\frac{r}{W(z)}\right) = \left(\sqrt{2} \frac{r}{W(z)}\right)^l \mathcal{L}_p^{(l)}\left(2 \frac{r^2}{W^2(z)}\right)$



Behavior of Laguerre-Gaussian modes

Each mode is a mere space modulation of the fundamental

$$q' = 1$$

same as HG modes


- Same equation for q as in the fundamental mode
- $W(z)$ and $R(z)$ retain their meanings and properties
- Rayleigh length and diffraction angle are unchanged

$$r \frac{\partial^2 g}{\partial r^2} - (l + 1 - x) \frac{\partial g}{\partial x} + pg = 0$$

- Solutions are, by definition, the orthogonal generalized Laguerre polynomials
- $\mathcal{L}_0^{(l)} = 1$, $\mathcal{L}_1^{(l)} = -x + l + 1$, $\mathcal{L}_2^{(l)} = \frac{x^2}{2} - (l + 2)x + \frac{(l+1)(l+2)}{2}$
- $\mathcal{L}_m^{(l)}$ has degree m
- $g\left(\frac{r}{W(z)}\right) = \left(\sqrt{2} \frac{r}{W(z)}\right)^l \mathcal{L}_p^{(l)}\left(2 \frac{r^2}{W^2(z)}\right)$

Intensity profiles of Laguerre Gaussian (LG) modes


The intensity is proportional to the squared envelope



$LG(0,0)$



$LG(0,1)$: vortex




$LG(0,2)$




Intensity profiles of other Laguerre Gaussian (LG) modes


The intensity is proportional to the squared envelope



$LG(1,2)$



$LG(1,3)$



$LG(2,3)$



Homogeneous phase shift is different for high order modes

$$qP' + (1 + m + n)j = 0$$

$$qP' + (1 + 2p + l)j = 0$$

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten



Homogeneous phase shift is different for high order modes

$$qP' + (1 + m + n)j = 0$$

$$qP' + (1 + 2p + l)j = 0$$

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten



Homogeneous phase shift is different for high order modes

$$qP' + (1 + m + n)j = 0$$

$$qP' + (1 + 2p + l)j = 0$$

A small phase difference between modes around the beam waist

- Slightly different optical paths for different orders
- Slightly different oscillating frequencies in lasers
- Usually forgotten. . . particularly in the next section



- 1 Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams



Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin **waist**: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi w_0}$$

Do geometrical optics deal with plane and spherical waves ?



Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are **seldom alone**: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?



Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- **A ray is a Poynting vector curve**
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

• Parallel rays imply a plane wavefront

• Converging or diverging rays imply a spherical wavefront

• A bunch of rays implies a Gaussian beam



Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A **bunch of rays** describes a **wavefront**

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

- Parallel rays imply a plane wavefront
- Converging or diverging rays imply a spherical wavefront



Geometrical optics framework

Where is is shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

- **Parallel** rays imply a **plane wavefront**
- Converging or diverging rays imply a spherical wavefront
- But neither of them has an infinite extension !



Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

- Parallel rays imply a plane wavefront
- **Converging** or diverging rays imply a **spherical wavefront**
- But neither of them has an infinite extension !



Geometrical optics framework

Where is it shown that rays are not so thin as you may think

Geometrical optics *do not* deal with thin rays

- A thin ray has a thin waist: it should diffract
- Thin rays are seldom alone: their meaning is collective
- A ray is a Poynting vector curve
- A bunch of rays describes a wavefront

$$\gamma = \frac{\lambda}{\pi W_0}$$

Do geometrical optics deal with plane and spherical waves ?

- Parallel rays imply a plane wavefront
- Converging or diverging rays imply a spherical wavefront
- **But neither of them has an infinite extension !**



Geometrical optic is Gaussian optics

Transversely limited plane waves

Parallel rays

Gaussian Beams **within their** Rayleigh zone

Transversely limited spherical waves

Con(Di)verging rays

Gaussian Beams **far from** their Rayleigh zone

Orders of magnitude

- He-Ne laser: $W_0 \approx 1\text{mm}$, $\lambda = 633\text{nm}$, $L_R \approx 5\text{m}$
- GSM Antenna: $W_0 \approx 1\text{m}$, $\lambda \approx 33\text{cm}$, $L_R \approx 10\text{m}$



Geometrical optic is Gaussian optics

Transversely limited plane waves

Parallel rays

Gaussian Beams **within their** Rayleigh zone

Transversely limited spherical waves

Con(Di)verging rays

Gaussian Beams **far from** their Rayleigh zone

Orders of magnitude

- He-Ne laser: $W_0 \approx 1\text{mm}$, $\lambda = 633\text{nm}$, $L_R \approx 5\text{m}$
- GSM Antenna: $W_0 \approx 1\text{m}$, $\lambda \approx 33\text{cm}$, $L_R \approx 10\text{m}$



Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

Descartes made paraxial

Paraxial approximation : $\theta \ll 1$

$$n_1 \theta_1 \approx n_2 \theta_2$$

Geometrical optics is linear algebra

- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly



Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

Descartes made paraxial

Paraxial approximation : $\theta \ll 1$

$$n_1 \theta_1 \approx n_2 \theta_2$$

Geometrical optics is linear algebra

- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly



Geometrical optics is linear

Geometrical optics stems entirely from Descartes law

$$n_1 \sin(\theta_1) = n_2 \sin(\theta_2)$$

Descartes made paraxial

Paraxial approximation : $\theta \ll 1$

$$n_1 \theta_1 \approx n_2 \theta_2$$

Geometrical optics is linear algebra

- Paraxial Descartes is linear
- Straight line propagation is linear
- The behavior of a ray through any optical system can be described linearly




Matrix geometrical optics

A 2 dimensional linear algebra framework

The ray vector $v = \begin{pmatrix} y \\ \theta \end{pmatrix}$

- y : distance from the axis
- θ : angle to the axis



An optical system $v' = Mv$

- M is a 2×2 real matrix
- It can describe any centered paraxial optical system




Matrix geometrical optics

A 2 dimensional linear algebra framework


The ray vector $v = \begin{pmatrix} y \\ \theta \end{pmatrix}$

- y : distance from the axis
- θ : angle to the axis



An optical system $v' = Mv$


- M is a 2×2 real matrix
- It can describe any centered paraxial optical system



Optical system composition

Optical system composition reduced to matrix product

Optical System Composition



Matrix Composition

- $v' = M_1 \cdot v$
- $v'' = M_2 \cdot v'$
- $v'' = M_2 M_1 \cdot v$

Complex systems


Compose simple systems



Optical system composition

Optical system composition reduced to matrix product

Optical System Composition



Matrix Composition

- $v' = M_1 \cdot v$
- $v'' = M_2 \cdot v'$
- $v'' = M_2 M_1 \cdot v$

Complex systems


Compose simple systems



Optical system composition

Optical system composition reduced to matrix product

Optical System Composition



Matrix Composition

- $v' = M_1 \cdot v$
- $v'' = M_2 \cdot v'$
- $v'' = M_2 M_1 \cdot v$

Complex systems

Compose simple systems



- 1 Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams



Propagation in a homogeneous medium


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_d \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Light propagates in straight line

- No direction change: $\theta' = \theta$
- $y' = y + d \sin(\theta)$

M_d

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & d \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Propagation in a homogeneous medium


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_d \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Light propagates in straight line

- No direction change: $\theta' = \theta$
- $y' = y + d \sin(\theta)$

M_d

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & d \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Passing through a plane interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_p \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

- No propagation: $y' = y$
- $n \sin(\theta) = n' \sin(\theta')$
- $\theta' \approx \frac{n}{n'} \theta$

M_p

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Passing through a plane interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_p \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

- No propagation: $y' = y$
- $n \sin(\theta) = n' \sin(\theta')$
- $\theta' \approx \frac{n}{n'} \theta$

M_p

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$




Passing through a thin lens

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_l \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Two characteristic rays

- No propagation: $y' = y$
- Blue ray: $y = 0 \Rightarrow \theta' = \theta$
- Red ray: $\theta = 0 \Rightarrow \theta' = -\frac{1}{f}y$



M_l

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Passing through a thin lens


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_l \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Two characteristic rays

- No propagation: $y' = y$
- Blue ray: $y = 0 \Rightarrow \theta' = \theta$
- Red ray: $\theta = 0 \Rightarrow \theta' = -\frac{1}{f}y$

M_l

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$




Passing through a (thin) spherical interface

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

- Thin interface
No propagation: $y' = y$
- Blue ray: $y \approx R\theta \Rightarrow \theta' = \theta$
- Red ray: $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$



Passing through a (thin) spherical interface

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

- Thin interface


No propagation: $y' = y$

- Blue ray: $y \approx R\theta \Rightarrow \theta' = \theta$
- Red ray: $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$

$$\theta' = ay + b\theta$$

Solve for (a, b) using

- $(y, \theta') = (R\theta, \theta)$
- $(y, \theta') = (0, \frac{n}{n'}\theta)$



Passing through a (thin) spherical interface


$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = M_s \begin{pmatrix} y \\ \theta \end{pmatrix}$$

Descartes

- Thin interface
No propagation: $y' = y$
- Blue ray: $y \approx R\theta \Rightarrow \theta' = \theta$
- Red ray: $y = 0 \Rightarrow \theta' \approx \frac{n}{n'}\theta$

M_s

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ \frac{n'-n}{n'R} & \frac{n}{n'} \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$




Mirrors

Unfolding the light


Plane mirrors as if they did not exist

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Spherical Mirrors are thin lenses

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{2}{R} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$




Mirrors

Unfolding the light


Plane mirrors as if they did not exist

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Spherical Mirrors are thin lenses

$$\begin{pmatrix} y' \\ \theta' \end{pmatrix} = \begin{bmatrix} 1 & 0 \\ -\frac{2}{R} & 1 \end{bmatrix} \begin{pmatrix} y \\ \theta \end{pmatrix}$$



Matrix property

A determinant property stemming from all the simple matrices determinants

n : start index

n' : stop index

$$\forall M, \det(M) = \frac{n}{n'}$$



- 1 Fundamentals of Gaussian beam propagation
 - Gaussian beams vs. plane waves
 - The fundamental mode
 - Higher order modes
- 2 Matrix methods for geometrical and Gaussian optics
 - Linear algebra for geometrical optics
 - A few simple matrices
 - Matrix method for Gaussian beams



Gaussian modes, propagation and lenses

A Gaussian mode does not change upon propagation or by passing through thin interfaces or lenses

$$g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

- z independent modulation of the fundamental mode
- Free space $q' = 1$ common property
- Thin lens does not change mode profile

Common $R(z)$ and $W(z)$ behavior

All the modes share the same laws on $q(z)$, $R(z)$ and $W(z)$



Gaussian modes, propagation and lenses

A Gaussian mode does not change upon propagation or by passing through thin interfaces or lenses

$$g\left(\frac{x}{W(z)}\right) h\left(\frac{y}{W(z)}\right) e^{-i\left(P(z) + \frac{k}{2q(z)}(x^2 + y^2)\right)}$$

- z independent modulation of the fundamental mode
- Free space $q' = 1$ common property
- Thin lens does not change mode profile

Common $R(z)$ and $W(z)$ behavior

All the modes share the same laws on $q(z)$, $R(z)$ and $W(z)$



Gaussian beam propagation: the ABCD law

The transformation of the complex radius q for simple optical systems

Free space

$$q' = 1$$

- $q_1 = q_0 + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$



Gaussian beam propagation: the ABCD law

The transformation of the complex radius q for simple optical systems

Free space


$$q' = 1$$

- $q_1 = q_0 + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$

Plane interface


$$n_0/n_1 = R_0/R_1$$

- $\frac{q_1}{q_0} = \frac{n_1}{n_0} \Rightarrow q_1 = \frac{1 \times q_0}{\frac{n}{n'}}$
- $M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n_0}{n_1} \end{pmatrix}$



Gaussian beam propagation: the ABCD law

The transformation of the complex radius q for simple optical systems



Thin lens

$$\frac{1}{R_1} = \frac{1}{R_0} - \frac{1}{f}$$

$$\bullet \frac{1}{q_1} = \frac{1}{q_0} - \frac{1}{f} \Rightarrow q_1 = \frac{1}{-\frac{1}{f}q_0 + 1}$$

$$\bullet M_l = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$$



Gaussian beam propagation: the ABCD law

The transformation of the complex radius q for simple optical systems

Free space

$$q' = 1$$

- $q_1 = q_0 + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$

Plane interface

$$n_0/n_1 = R_0/R_1$$

- $\frac{q_1}{q_0} = \frac{n_1}{n_0} \Rightarrow q_1 = \frac{1 \times q_0}{\frac{n}{n'}}$
- $M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n_0}{n_1} \end{pmatrix}$

Thin lens

$$\frac{1}{R_1} = \frac{1}{R_0} - \frac{1}{f}$$

- $\frac{1}{q_1} = \frac{1}{q_0} - \frac{1}{f} \Rightarrow q_1 = \frac{1}{-\frac{1}{f}q_0 + 1}$
- $M_l = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$

Kogelnik's ABCD law

$$M = \begin{pmatrix} A & B \\ C & D \end{pmatrix} \Rightarrow q_1 = \frac{Aq_0 + B}{Cq_0 + D}$$



Gaussian beam propagation: the ABCD law

The transformation of the complex radius q for simple optical systems

Free space

$$q' = 1$$

- $q_1 = q_0 + d$
- $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$

Thin lens

$$\frac{1}{R_1} = \frac{1}{R_0} - \frac{1}{f}$$

- $\frac{1}{q_1} = \frac{1}{q_0} - \frac{1}{f} \Rightarrow q_1 = \frac{1}{-\frac{1}{f}q_0 + 1}$
- $M_l = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$

Plane interface

$$n_0/n_1 = R_0/R_1$$

- $\frac{q_1}{q_0} = \frac{n_1}{n_0} \Rightarrow q_1 = \frac{1 \times q_0}{\frac{n_1}{n_0}}$
- $M_p = \begin{pmatrix} 1 & 0 \\ 0 & \frac{n_0}{n_1} \end{pmatrix}$

Kogelnik's ABCD law

$$M = \begin{pmatrix} A & B \\ C & D \end{pmatrix} \Rightarrow q_1 = \frac{Aq_0 + B}{Cq_0 + D}$$

Geometrical and Gaussian optics are linked through paraxial approx.

Gaussian beam propagation can be evaluated, for **any** mode, using simple matrix geometrical optics




Focal lens example

Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam

- Input plane : just before lens
- Output plane : after length d
- Input beam at waist:

$$q_0 = i \frac{\pi W_0^2}{\lambda}$$



Focal lens example


Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam

- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R_0}$

Propagation matrix

- lens: $M_f = \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix}$
- distance d : $M_d = \begin{pmatrix} 1 & d \\ 0 & 1 \end{pmatrix}$



Focal lens example


Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam

- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R0}$

Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$



Focal lens example

Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam


- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R_0}$

Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$

ABCD law

$$q_1 = \frac{df + i(f - d)L_{R_0}}{f - iL_{R_0}}$$



Focal lens example

Using the ABCD law to verify that parallel rays do converge on the focal plane

Parallel input beam


- Input plane : just before lens
- Output plane : after length d
- Input beam at waist: $q_0 = iL_{R0}$

Propagation matrix

$$M_d \cdot M_f = \begin{pmatrix} -\frac{d}{f} + 1 & d \\ -\frac{1}{f} & 1 \end{pmatrix}$$

ABCD law

$$q_1 = \frac{df + i(f - d)L_{R0}}{f - iL_{R0}}$$



d for plane wavefront: imaginary q_1

$$d = \frac{f}{1 + \left(\frac{f}{L_{R0}}\right)^2}$$

Transformation of a parallel beam by a lens

The basics of geometrical optics

As we just saw


$$L_{R_0} \ll d$$

$$q_1 = \frac{df + i(f - d)L_{R_0}}{f - iL_{R_0}} \quad \& \quad d \approx f$$

Identifying W_1 in q_1

$$L_{R_0} \ll d$$

$$W_1 = \frac{\lambda|f|}{\pi W_0}$$



Transformation of a parallel beam by a lens


The basics of geometrical optics

As we just saw $L_{R_0} \ll d$

$$q_1 = \frac{df + i(f - d)L_{R_0}}{f - iL_{R_0}} \quad \& \quad d \approx f$$

Identifying W_1 in q_1 $L_{R_0} \ll d$


$$W_1 = \frac{\lambda|f|}{\pi W_0}$$



Transformation of a diffracting Gaussian beam by a lens

From $-f - a$ to $f + b$

- Input $q_0 = iL_{R_0}$ at $-f - a$
- Output q_1 at $f + b$
- Assume $L_{R_0} \ll a$ and $L_{R_1} \ll b$



Propagation Matrix

$$\begin{pmatrix} 1 & f+b \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix} \begin{pmatrix} 1 & f+a \\ 0 & 1 \end{pmatrix} = \begin{pmatrix} -\frac{b}{f} & -\frac{ab-f^2}{f} \\ -\frac{1}{f} & -\frac{a}{f} \end{pmatrix}$$

From waist to waist

assuming q_1 imaginary

$$ab = f^2$$


$$\left(\frac{w_1}{w_0} \right)^2 = \frac{b}{a}$$



Transformation of a diffracting Gaussian beam by a lens

From $-f - a$ to $f + b$

- Input $q_0 = iL_{R_0}$ at $-f - a$
- Output q_1 at $f + b$
- Assume $L_{R_0} \ll a$ and $L_{R_1} \ll b$



Propagation Matrix

$$\begin{pmatrix} 1 & f+b \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix} \begin{pmatrix} 1 & f+a \\ 0 & 1 \end{pmatrix} = \begin{pmatrix} -\frac{b}{f} & -\frac{ab-f^2}{f} \\ -\frac{1}{f} & -\frac{a}{f} \end{pmatrix}$$

From waist to waist

assuming q_1 imaginary

$$ab = f^2$$


$$\left(\frac{w_1}{w_0} \right)^2 = \frac{b}{a}$$



Transformation of a diffracting Gaussian beam by a lens

From $-f - a$ to $f + b$

- Input $q_0 = iL_{R_0}$ at $-f - a$
- Output q_1 at $f + b$
- Assume $L_{R_0} \ll a$ and $L_{R_1} \ll b$



Propagation Matrix

$$\begin{pmatrix} 1 & f+b \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 \\ -\frac{1}{f} & 1 \end{pmatrix} \begin{pmatrix} 1 & f+a \\ 0 & 1 \end{pmatrix} = \begin{pmatrix} -\frac{b}{f} & -\frac{ab-f^2}{f} \\ -\frac{1}{f} & -\frac{a}{f} \end{pmatrix}$$

From waist to waist

assuming q_1 imaginary

$$ab = f^2$$

$$\left(\frac{w_1}{w_0} \right)^2 = \frac{b}{a}$$