

#### Principles of Kelvin Probe Force Microscopy and applications

Laurent Nony

#### ▶ To cite this version:

Laurent Nony. Principles of Kelvin Probe Force Microscopy and applications. DEA. Laurent NONY, 1st German-French Summer School on noncontact -AFM Porquerolles, 6th-11th 2013, France, 2013, pp.80. cel-00917935

#### HAL Id: cel-00917935 https://cel.hal.science/cel-00917935

Submitted on 12 Dec 2013

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# **PRINCIPLES OF KELVIN PROBE FORCE MICROSCOPY** AND APPLICATIONS

Laurent NONY

Aix-Marseille Université, Faculté des Sciences, site Etoile - Saint-Jérôme IM2NP, UMR CNRS 7334 Marseille, France

laurent.nony@im2np.fr

1<sup>st</sup> German-French Summer School on noncontact -AFM Porquerolles, 6<sup>th</sup>-11<sup>th</sup> of October 2013, France



Institut Matériaux Microélectronique Nanosciences de Provence













 $KPFM \rightarrow Electrostatic$  force compensation  $\rightarrow V_{bias} \rightarrow Models$  to quantitative estimates







# Outline

#### Ι. INTRODUCTION

Electrostatic forces & Contact Potential Difference (CPD) 

#### Ш. PRINCIPLES OF KPFM

- **Fundamentals of KPFM**
- KPFM operational mode: FM and AM mode

#### III. ELECTROSTATIC MODELS

- Single charge trapped within a capacitor
- Assemblies of charge on a bulk insulator

#### IV. APPLICATIONS

- Metals including charged adsorbates
- Bulk insulators with and without charged adsorbates
- **HIGH-RESOLUTION KPFM** V.

□ Short-range electrostatic forces & concept of Local CPD (LCPD) **CONCLUSION** 











# I. Introduction



Institut Matériaux Microélectronique Nanosciences de Provence











### Electrostatic forces: macroscopic concept





Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









# Electrostatic forces: macroscopic concept



William Thomson (later Lord Kelvin of Largs): 1824 (Belfast, Ireland) - 1907 (Largs, UK)



$$I_{\rm dc} = \frac{dC}{dt} (V_{\rm bias} - V_{\rm offs})$$

\*Lord Kelvin, Phil. Mag. 46, 82 (1898)



Institut Matériaux Microélectronique Nanosciences de Provence











#### Electrostatic forces: macroscopic concept

Electrostatic force acting on the plates of a charged parallel-plate capacitor:



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var

POLYTECH

### Surface dipole & work function in metals

K. Wandelt, Appl. Surf. Sci. 111, 1 (1997)

"The work function  $\varphi$  of an **infinite homogeneous metal** surface is defined as the energy difference between... the Fermi level... and a final state... the so called vacuum level."



















 $V_{\text{bias}} = V_{\text{CPD}} \rightarrow electrostatic force compensation$ 



Institut Matériaux Microélectronique Nanosciences de Provence









10



$$\mathbf{F}_{\rm tip}^{\rm el} = +\frac{\partial W^{\rm el}}{\partial z} \widehat{\mathbf{z}} = +\frac{1}{2} \frac{\partial C}{\partial z} V^2 \widehat{\mathbf{z}} = +\frac{1}{2} \frac{\partial C}{\partial z} (V_{\rm bias} - V_{\rm CPD})^2 \widehat{\mathbf{z}}$$

□ The essence of KPFM is to detect <u>electrostatic forces</u> between tip and surface and to compensate them by applying the proper dc bias on the sample during scanning :

$$F_{\rm tip}^{\rm el} = 0 \Leftrightarrow V_{\rm bias} = V_{\rm CPD}$$

□ This is why KPFM may be used on <u>any kind of surfaces</u>: metals, semiconductors & insulators, despite with the former the concept of CPD is ambiguous...











$$\mathbf{F}_{\rm tip}^{\rm el} = +\frac{\partial W^{\rm el}}{\partial z}\widehat{\mathbf{z}} = +\frac{1}{2}\frac{\partial C}{\partial z}V^2\widehat{\mathbf{z}} = +\frac{1}{2}\frac{\partial C}{\partial z}(V_{\rm bias} - V_{\rm CPD})^2\widehat{\mathbf{z}}$$

□ Electr. forces may either stem from charges or dipoles (ions, vacancies, clusters, charge transfer within molecules...) at the tip-surface interface



Aix\*Marseille

POLYTECH



$$\mathbf{F}_{\mathrm{tip}}^{\mathrm{el}} = +\frac{\partial W^{\mathrm{el}}}{\partial z}\widehat{\mathbf{z}} = +\frac{1}{2}\frac{\partial C}{\partial z}V^{2}\widehat{\mathbf{z}} = +\frac{1}{2}\frac{\partial C}{\partial z}(V_{\mathrm{bias}} - V_{\mathrm{CPD}})^{2}\widehat{\mathbf{z}}$$

□ Therefore, KPFM was thought as a mean to measure CPD\* variations between tip and surface:

$$F_{\rm tip}^{\rm el} = 0 \Leftrightarrow V_{\rm bias} = V_{\rm CPD}$$

**BUT** this relies on two (major) assumptions:

- the force must depend quadratically on the effective applied bias V
- V (hence, V<sub>CPD</sub>) must not depend on z

\* only if the tip is grounded and V is applied to the sample,  $V_{\text{bias}} = -V_{CPD}$  otherwise



Institut Matériaux Microélectronique Nanosciences de Provence









#### Sign of the charge & dipole orientation\*



#### $\Box$ q > 0 (<0): negative (positive) shift of V<sub>CPD</sub> w.r.t. V<sub>CPD.ref</sub> □ $\uparrow$ (↓) : negative (positive) shift of V<sub>CPD</sub> w.r.t. V<sub>CPD,ref</sub>

\*consistent with most frequently reported results (see « References » section at the end of the slides)



Institut Matériaux Microélectronique Nanosciences de Provence









15

# Example

#### $\Box$ ZnPcCl<sub>8</sub> on Ag(111)<sup>1</sup>:



- V<sub>CPD, ref</sub> = 4.73 V
- $V_{CPD, P1} = V_{CPD, ref} 103 \text{ mV} \rightarrow \text{interf. dip. decreased} \rightarrow \text{c.t. to the sample} \rightarrow \text{layer gets} + \text{charged}$
- $V_{CPD, P2} = V_{CPD, ref}$ -54 mV  $\rightarrow$  idem, but less than with P1

<sup>1</sup>P. Milde et al. Nanotechnology 19, 305501 (2008)





# **II. Principles of KPFM**



Institut Matériaux Microélectronique Nanosciences de Provence









#### **Concepts of non contact-AFM**



F.Giessibl, Phys Rev. B 56, 16010 (1997); Phys. Rev.B 61, 9968 (2000)

Institut Matériaux Microélectronique Nanosciences de Provence Im2np







## Concepts of non contact-AFM













19











Ideally, the only option to perform accurate and « intrumentation-free » forces & CPD measurements is to do 4D force fields measurements:



but « ideal situations » don't exist...



Institut Matériaux Microélectronique Nanosciences de Provence











## Concepts of non contact-AFM











Idea<sup>1</sup>: bias modulation

discrimination of the electrostatic force w.r.t. other interaction forces



Attractive electrostatic force (tip):

$$F_{\rm tip}^{\rm el} = +\frac{1}{2} \frac{\partial C(z)}{\partial z} \left[ V_{\rm dc} - V_{\rm CPD} + V_{\rm ac} \sin(2\pi f_{\rm mod} t) \right]^2$$

<sup>1</sup>M. Nonnenmacher et al., APL **58**, 2921 (1991); J. Weaver et al. JVSTB **9**, 1559 (1991)









Spectral components:

$$\begin{cases} F_{\rm tip}^{\rm el,0} = \frac{\partial C(z)}{\partial z} \left[ \frac{1}{2} \left( V_{\rm dc} - V_{\rm CPD} \right)^2 + \frac{V_{\rm ac}^2}{4} \right] \\ F_{\rm tip}^{\rm el,fmod} = \frac{\partial C(z)}{\partial z} \left( V_{\rm dc} - V_{\rm CPD} \right) V_{\rm ac} \sin(2\pi f_{\rm mod} t) \\ F_{\rm tip}^{\rm el,2fmod} = \frac{\partial C(z)}{\partial z} \frac{V_{\rm ac}^2}{4} \cos(2f_{\rm mod} t) \end{cases}$$

These superimpose to the interaction force between the cantilever and the surface

 $\Box$  Static deflection & induced vibrations of the cantilever at  $f_0 + f_{mod}$  and  $f_0 + 2f_{mod}$ 

Detection and cancellation of the f<sub>mod</sub> component by applying a proper dc voltage which matches the CPD















<sup>1</sup>U.Zerweck et al., Phys. Rev. B 71, 125424 (2005)





## KPFM operational modes: FM- & AM-KPFM



26

# **Frequency-Modulation KPFM: concept**



# FM-KPFM is sensitive to the electrostatic force gradient (?)











### **Frequency-Modulation KPFM: concept**



 Institut Matériaux Microélectronique Nanosciences de Provence

 UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









### **Frequency-Modulation KPFM: concept**













# Frequency-modulation KPFM: experimental setup





Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









Frequency-modulation KPFM: experimental setup



<sup>1</sup>Kelvin Probe Force Microscopy, Measuring & Compensating Electrostatic forces, Springer Series in Surface Sciences (Th. Glatzel & S. Sadewasser Ed.)

Institut Matériaux Microélectronique Nanosciences de Provence Im2np









# Frequency-modulation KPFM: temporal considerations



- □  $f_{mod}$  has to be within the demodulation bandwidth of the PLL → compromise:
  - extending the PLL bandwidth  $\rightarrow$  adds noise to  $\Delta f$  detection
  - must remain large enough to not influence the z regulation (usually requires to slow down the scans)
  - order of magnitude: 1 kHz













# **Amplitude-Modulation KPFM: concept**

 $F_{el}$  is now modulated at the frequency of the first bending eigenmode of the cantilever :  $f_{mod} \sim 6.3 f_0 \sim 1 \text{ MHz}$ 



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









33

#### **Amplitude-Modulation KPFM: concept**



# Amplitude-modulation KPFM: experimental setup





Institut Matériaux Microélectronique Nanosciences de Provence









35
## Amplitude-modulation KPFM: temporal considerations



## AM- vs. FM-KPFM

### PHYSICAL REVIEW B 86, 075407 (2012)

### Multiscale approach for simulations of Kelvin probe force microscopy with atomic resolution

Ali Sadeghi, Alexis Baratoff, S. Alireza Ghasemi, Stefan Goedecker, Thilo Glatzel, Shigeki Kawai, and Ernst Meyer Department of Physics, University of Basel, Klingelbergstrasse 82, CH-4056 Basel, Switzerland (Received 23 March 2012; revised manuscript received 21 June 2012; published 2 August 2012)

The distance dependence and atomic-scale contrast recently observed in nominal contact potential difference (CPD) signals simultaneously recorded by Kelvin probe force microscopy (KPFM) using noncontact atomic force microscopy (NCAFM) on defect-free surfaces of insulating as well as semiconducting samples have stimulated theoretical attempts to explain such effects. Especially in the case of insulators, it is not quite clear how the applied bias voltage affects electrostatic forces acting on the atomic scale. We attack this problem in two steps. First, the electrostatics of the macroscopic tip-cantilever-sample system is treated by a finite-difference method on an adjustable nonuniform mesh. Then the resulting electric field under the tip apex is inserted into a series of atomistic wavelet-based density functional theory (DFT) calculations. Results are shown for a realistic neutral but reactive silicon nanoscale tip interacting with a NaCl(001) sample. Bias-dependent forces and resulting atomic displacements are computed to within an unprecedented accuracy. Theoretical expressions for amplitude modulation (AM) and frequency modulation (FM) KPFM signals and for the corresponding local contact potential differences (LCPD) are obtained by combining the macroscopic and atomistic contributions to the electrostatic force component generated at the voltage modulation frequency, and evaluated for several tip oscillation amplitudes A up to 10 nm. For A = 0.1 Å, the computed LCPD contrast is proportional to the slope of the atomistic force versus bias in the AM mode and to its derivative with respect to the tip-sample separation in the FM mode. Being essentially constant over a few volts, this slope is the basic quantity that determines variations of the atomic-scale LCPD contrast. Already above A = 1 Å, the LCPD contrasts in both modes exhibit almost the same spatial dependence as the slope. In the AM mode, this contrast is approximately proportional to  $A^{-1/2}$ , but remains much weaker than the contrast in the FM mode, which drops somewhat faster as A is increased. These trends are a consequence of the macroscopic contributions to the KPFM signal, which are stronger in the AM-mode and especially important if the sample is an insulator even at subnanometer separations where atomic-scale contrast appears.



Institut Matériaux Microélectronique Nanosciences de Provence









37

## AM- vs. FM-KPFM

	FM-KPFM	AM-KPFM
Pros	<ul> <li>Ease of implementation</li> <li>CPD contrast larger than AM- in the large amplitude regime</li> </ul>	<ul> <li>Better S/N ratio than FM- KPFM</li> <li>More sensitive to capacitive contributions involved in high-resolution CPD imaging</li> <li>CPD atomic-scale contrast reported</li> </ul>
Cons	<ul> <li>Low bandwidth, slow, unless sidebands are used (but LIA input to be amplified)</li> </ul>	<ul> <li>Implementation more demanding (2<sup>nd</sup> PLL)</li> <li>Large detector bandwidth required with usual cantilevers (~1 MHz)</li> </ul>











# **III. Electrostatic models**











# 1 - A charge trapped within the capacitor<sup>1</sup>

Double capacitance model<sup>1</sup>:



<sup>1</sup>Nanoelectronics and Information Technology: Advanced Electronic Materials and Novel Devices, edited by R. Waser (John Wiley & Sons, New York, 2003); R. Stomp et al., Pys. Rev. Lett. 94, 056802 (2005); J. Polesel et al., Nanotechnology 15, S24 (2004)



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









40

## 1 - A charge trapped within the capacitor<sup>1</sup>



Institut Matériaux Microélectronique Nanosciences de Provence CARNOI Universitée Aix-Marseille et Sud Toulon-Var

Im2np





What about polarisability ?!?

## 1 - A charge trapped within the capacitor<sup>1</sup>









## 2 - An assembly of charges trapped within the capacitor<sup>1</sup>

Interaction force : 
$$F(z) = F_{lr}(z) + F_{es}(z) + F_{sr}(z)$$
 with  $F_{es} = \int_{tip} \frac{\sigma^2}{2\epsilon_0} \hat{n} \cdot \hat{u}_z dS$ 

Building the analytic approach to  $F_{es}$ :



☑ Crystal surface has a perfect fcc structure, carrying neither local charge nor dipole

✓ The Madelung potential expands at the surface<sup>2</sup>, although decaying exponentially fast



✓ Tip apex: microscopic structure (nano-asperity, area 1, radius R<sub>a</sub>) + mesoscopic half-sphere (area 2, radius R): METALLIC
 ✓ Sample: topmost infinite layer of alternate point charges + bulk treated as a continuous medium

Surface charge density that develops on the tip has 2 origins:

- ${\ensuremath{\sc w}}$  Madelung surface potential-mediated contribution (microsc.):  $\sigma_{\!\!\mu}$
- Z<sub>m</sub> ☑ Description of the ionic polarization of the sample , selfconsistency

Classical approach

<sup>1</sup>F. Bocquet *et al.*, Phys. Rev. B **78**, 035410 (2008); <sup>2</sup> R.Watson *et al.*, Phys. Rev. B **24**, 1791 (1981)



































$$F_{es} = \int_{\text{tip}} \frac{\left(\sigma_m + \sigma_\mu\right)^2}{2\epsilon_0} \widehat{n}.\widehat{u}_z d\mathcal{S} = F_m + F_{m\mu} + F_\mu$$

 $F_{m} : \text{negligible (counter-eletrode too far)}$   $F_{m\mu}^{(2)} : \text{capacitive coupling on the mesoscopic part of the tip decays fast; negligible compared to <math>F_{m\mu}^{(0)}$ ; tip enhancement effect  $F_{\mu}^{(1)}$  : negligible compared to  $F_{\mu}^{(2)}$  (not obvious, geometry dependent)  $F_{es} = F_{m\mu}^{(1)} + F_{\mu}^{(2)}$ 

$$F_{es}(V_b) = B \times V_b \exp\left\{-\frac{2\pi}{a'}z_\mu\right\} \times \left[\cos(\tilde{x_0}) + \cos(\tilde{y_0})\right] + (AV_b^2 + C) \times \exp\left\{-\frac{4\pi}{a'}z_\mu\right\}$$
with  $V_b = V_{dc} + V_{ac}\sin(2\pi f_K t)$  short-range electrostatic force

 Institut Matériaux Microélectronique Nanosciences de Provence
 Institut Carnoi

 UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var
 Image: Constitut Carnoi



(Aix\*Marseille universite

CITS



isen

POLYTECH

## Summary

In general, the electrostatic has the form:

$$F^{\rm el} = AV_{\rm bias}^2 + BV_{\rm bias} + C$$

Hence, the f<sub>mod</sub>-modulated component has the form:

$$F^{\mathrm{el},f_{\mathrm{mod}}} = \left[B + 2A(V_{\mathrm{dc}} - V_{\mathrm{CPD}})\right] V_{\mathrm{ac}} \sin(2\pi f_{\mathrm{mod}}t)$$

Therefore:

$$V_{\rm dc} = V_{\rm CPD} - \frac{B}{2A}$$

- The measured « CPD » conceals the physics of the interface • (parameters A & B): capacitance, charges, dipoles...
- B and A may be tip geometry and distance dependent... •























# **IV.** Applications













#### Thin insulating films :

## KCl on Au(111)<sup>1</sup> (FM-KPFM):



□ KCI islands decrease the CPD: interface dipole decreased (c.t. to the sample)

- **Quantitative measurement of the CPD when adsorbates are larger than** the tip radius
  - result confirmed in the literature (see "References" section)

<sup>1</sup>U. Zerweck *et al.*, Phys. Rev. B **71**, 125424 (2005);











□ Thin insulating films :

lonic thin films on Au(111)<sup>1</sup> (FM-KPFM):





Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var





## □ <u>Molecular films</u> :





M=Cu, Co

- Molecular resolution in KPFM
- +30mV positive shift, increase of the interface dipole, c.t. to the layer
- Results interpreted in terms of electrostatic MS interaction

<sup>1</sup>T. Ichii *et al.*, JAP **107** 024315 (2010);



Institut Matériaux Microélectronique Nanosciences de Provence







POLYTECH



- □ <u>Molecular films</u> :
- C<sub>60</sub> on Ag(111)<sup>1</sup> (FM-KPFM):



- C<sub>60</sub> layers increase the CPD: interface dipole increase, c.t. to the molecules
- Behavior which depends on the nature of the metal
- Results compliant with macroscopic KPM

<sup>1</sup>U. Zerweck et al., Nanotechnology **18** 084006 (07); Hayashi et al., JAP **92**, 3784 (02)











## **KPFM on bulk insulators**

## □ <u>Mixed ionic crystals</u><sup>1</sup>: NaCl(001)+1% KCl (FM-KPFM)



□ Significant positive CPD shift at the step edges (+300 mV)

□ Local (-) charges are heterogeneously trapped along the step edges : not intrinsic

□ Similar behavior on other alkali halides (KCI)

Origin of these charges?

<sup>1</sup>C. Barth et al., Nanotechnology 17, S155 (2006)













## **KPFM on bulk insulators**

## □ <u>KCI(001)</u><sup>1</sup>: (FM-KPFM)



# "Double layer surface" effect<sup>2</sup> □ lonic crystals are extrinsic : Ca<sup>2+</sup> impurities nearby steps below the surface □ Global charge of the crystal is neutral → V<sup>-</sup> centers (cationic vacancies) □ Net negative charge nearby (below) step edges and kink sites



<sup>1</sup>C. Barth et al., Phys. Rev. Lett. 98, 136804 (2007); <sup>2</sup>J. Frenkel, Kinetic Theory of Liquids, (Clarendon Press, Oxford, 1946).



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









## KPFM on bulk insulators including molecular films

## CyanoPorphyrin on KBr(001) +Au<sup>1</sup>: (AM-KPFM)



## KPFM on bulk insulators including molecular films



# Triphenylene derivative on KBr(001)<sup>1</sup>: (FM-KPFM) (a) (b) MLh



- Two kinds of adsorption: flat (h) and vertical (v)
- Both domains exhibit lower CPDs than KBr: surface dipole increase
- h-domains consist of molecules interacting electrostatically with the substrate via polar CN groups

<sup>1</sup>A. Hinaut et al., J. Beilstein Nanotech. 3, 221 (2012)



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









# V. High-resolution KPFM











## Surface dipole & work function in metals

K. Wandelt, Appl. Surf. Sci. 111, 1 (1997)

"The work function  $\varphi$  of an **infinite homogeneous metal** surface is defined as the energy difference between... the Fermi level... and a final state... the so called vacuum level."



"...**Real (metallic) surfaces** are (a) of limited size, (b) made up by discrete atoms, (c) mostly include chemical and structural defects... Consequently  $\Phi(z)$  ... vary parallel to the surface. A few Å away from the surface, the energy difference  $\varphi_{loc}=\Delta\Phi(x,y,z)-\mu$  acquires the character of a **local work function**"



Local Contact Potential Difference (LCPD) = Short-Range Electrostatic forces







## High-resolution KPFM: semiconductor surfaces

## S. Kitamura et al., Appl. Surf. Sci. 157, 222 (2000) : Au/Si(111) 7x7



"The potential difference of atomic structures...does not seem to reflect the work function as we initially expected. It is therefore considered that the atomic potential difference reflects the local electron density on the surface."

## K. Okamoto *et al.*, Appl. Surf. Sci. **210**, 128 (2003) : Si(111)5√3x5√3-Sb





### First attempt to identify species of individual atoms by KPFM

Potential of adatoms (surface potential) : V<sub>Si</sub> ~ V<sub>Sb</sub>-0.2V "This value disagrees with the theoretical work functions of Si and Sb in bulk state...Our result indicates that KPFM on atomic scale does not measure the energy of the HOMO level."















## High-resolution KPFM: bulk insulators

□ <u>KBr(001)</u><sup>1</sup>: T.Glatzel (Basel, AM-KPFM)



<sup>1</sup>F.Bocquet et al., Phys. Rev. B **78**, 035410 (2008);













## High-resolution KPFM: charge state of individual atoms

## Measuring the Charge State of an Adatom with Noncontact Atomic Force Microscopy

Leo Gross,<sup>1</sup>\* Fabian Mohn,<sup>1</sup> Peter Liljeroth,<sup>1,2</sup> Jascha Repp,<sup>1,3</sup> Franz J. Giessibl,<sup>3</sup> Gerhard Meyer<sup>1</sup> 12 JUNE 2009 VOL 324 **SCIENCE** 



Topographic sensitivity to the charge state on the atomic scale



Spectroscopic sensitivity to the charge state on the atomic scale







Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var





## High-resolution KPFM: intramolecular resolution

nature nanotechnology

PUBLISHED ONLINE: 26 FEBRUARY 2012 | DOI: 10.1038/NNANO.2012.20

LETTERS

## Imaging the charge distribution within a single molecule

Fabian Mohn\*, Leo Gross, Nikolaj Moll and Gerhard Meyer









## **High-resolution KPFM: modelling**





Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var











POLYTECH'



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var

Im2np



Aix\*Marseille université

POLYTECH'

## SRE forces: influence of the polarization





 Institut Matériaux Microélectronique Nanosciences de Provence

 UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var



Aix\*Marseille université

POLYTECH

## SRE forces: influence of the polarization

Metallic sample hol

**Given Series 1.1** Force vs.  $V_b$  at z = 4.5 Å:





Aix\*Marseille

POLYTECH

isen

## SRE forces: influence of the polarization



- ✓ Bias modulation  $\rightarrow$  both electronic & ionic polarization (ionic displacements)
- $\checkmark$  Self-consistent coupling between SRE & chemical forces



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var









letallic sample ho

# LCPD atomic-scale contrast

## □ nc-AFM/KPFM simulator:

- ✓ Cantilever:  $A_0 = 8 \text{ nm p-p}$ ;  $f_0 = 150 \text{ kHz}$ ;  $k_c=30\text{N/m}$ ; Q = 30000
- ✓ FM-KPFM:  $V_{AC}$  = 0.5 V;  $f_{mod}$  = 1 kHz
- ✓ Scan speed : 1.5 s/line

### Constant $\Delta f$ = - 47.22 Hz (z<sub>start</sub> ~ 0.45 nm)



- ✓ Simultaneous atomic scale contrast in topography & CPD
- ✓ Contrast magnitude compliant with experimental data (30pm, 0.1V)
- $\checkmark$  Cross talk between topography & CPD when performing experiments at constant  $\Delta f$






























# Charge state of a single atom





Force  $\rightarrow \Delta f = -\frac{f_0}{2k} \frac{\partial F}{\partial z}$ 

 $\Delta f$  derived from the total force (LR+SR components, z = 5.1 Å, R = 50 Å)









POLYTECH

### Charge state of a single atom













# Conclusion



Institut Matériaux Microélectronique Nanosciences de Provence











#### Take home message

**Context: KPFM &** nc-AFM in UHV, distance to the surface ~ < 1 nm, large amplitudes, metallic samples covered with a thin dielectric or bulk insulators

- □ Compensating electrostatic forces is required for high-resolution nc-AFM imaging  $\rightarrow$  necessity for using KPFM
- □ Technic adds further complexity to the experimental setup but...■
- There is no obvious reason for choosing FM- rather than AM-KPFM mode so far...
- The sign of the charges or the dipole orientation of the species trapped within the capacitance which shift the CPD w.r.t. CPD<sub>ref</sub> (background) is easy to determine
- BUT getting quantitative numbers out of the experimental data is difficult (requires complex models) as the CPD is tip and distance dependent
- □ SRE forces yield a spatially-consistent map of the local CPD, but...



Institut Matériaux Microélectronique Nanosciences de Provence UMR CNRS 7334, Universités Aix-Marseille et Sud Toulon-Var







## Key references used for this talk

- W. Melitz et al., Kelvin Probe Force Microscopy and its application, Surf. Sci. Rep. 66, 1-27 (2011) •
- Kelvin Probe Force Microscopy, Measuring & Compensating Electrostatic forces, Springer Series in Surface Sciences (Th. Glatzel & S. Sadewasser Ed.)
- B.D. Terris et al., *Contact electrification using force microscopy*, Phys. Rev. Lett. **63**, 2669 (1989) ٠
- R. Stomp et al., Detection of single-electron charging in an individual InAs quantum dot by • noncontact atomic-force microscopy, Phys. Rev. Lett. 94, 056802 (2005)
- Y. Azuma et al., Phys. Rev. Lett. 96, 016108 (2006) •
- L. Gross et al. Measuring the charge state of an adatom with noncontact atomic force microscopy, • Science 324 :1428–1431 (2009)
- F. Mohn et al. *Imaging the charge distribution within a single molecule*, Nature Nanotechnology **7(4)**, • 227-231 (2012)
- C. Barth et al., AFM tip characterization by kelvin probe force microscopy, New J. Phys. 12, 093024 • (2010)
- H. Jacobs et al. J. Appl. Phys. 84, 1168 (1998). ٠
- J. Colchero et al. Phys. Rev. B 64, 245403 (2001). •
- T. Glatzel et al. Appl. Surf. Sci. 210, 84 (2003). ٠
- A. Gil et al. Nanotechnology 14, 332 (2003). ٠
- K. Sajewicz et al. Jap. J. Appl. Phys. 49, 025201 (2010). ٠













#### **Acknowledgements**

Ch. Loppacher (Pr.), F. Bocquet (MC), L.Nony (MC), F. Para (IE), A. Amrous (PhD)





Institut Matériaux Microélectronique Nanosciences de Provence









79